



SPECIFICATIONS

Socket	4.6
Socket	8-pin x 2
Socket	1
Socket	1
Socket	8GB GDDR6
Socket	Y
Socket	Y
Socket	5888 Units
Socket	GeForce RTX™ 3070 VENTUS 2X OC
Socket	7680x4320
Socket	DisplayPort x 3 (v1.4a) / HDMI™ 2.1 x 1
Socket	Y
Socket	650W
Socket	12 API
Socket	220W
Socket	4
Socket	1/1
Socket	832g / 1255g
Socket	232 x 124 x 52 mm
Socket	NVIDIA® GeForce RTX™ 3070
Socket	PCI Express® Gen 4
Socket	256-bit
Socket	1755 MHz
Socket	14 Gbps
Socket	Y
Core Clocks	Boost: Up to 2669 MHz Game: Up to 2447 MHz
Núcleos	2048 Units
Memoria	8GB GDDR6
Output	DisplayPort x 3 (v1.4a) / HDMI™ x 1 (Supports 4K@120Hz/8K@60Hz and VRR as specified in HDMI™ 2.1)
Motor de gráficos	AMD Radeon™ RX 6650 XT
Máximo de pantallas	4
FreeSync™ Technology	Y
Resolución máxima digital	7680x4320
Alimentación recomendada (W)	500 W or greater
Apto para Realidad Virtual	Y

FEATURES



Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.




Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 3.0

The award-winning MSI TORX Fan 3.0 design creates high static pressure and pushes the limits of thermal performance.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Thermal Padding

An abundance of thermal pads use any chance for additional heat transfer directly from the components.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Conectores de alimentación	8-pin x 1
Soporte OpenGL Versión	4.6
Dimensiones (mm)	235 x 125 x 47 mm

CONNECTIONS

