



SPECIFICATIONS

Socket	1/1
Socket	323 x 140 x 56mm
Socket	NVIDIA® GeForce RTX™ 3070
Socket	7680x4320
Socket	Y
Socket	Y
Socket	Y
Socket	4
Socket	4.6
Socket	12 API
Socket	1441g / 2269g
Socket	650W
Socket	GeForce RTX™ 3070 GAMING X TRIO
Socket	8-pin x2
Socket	240W
Socket	Y
Socket	DisplayPort x 3 (v1.4a) / HDMI™ 2.1 x1
Socket	256-bit
Socket	8GB GDDR6
Socket	14 Gbps
Socket	Boost: 1830 MHz
Socket	5888
Socket	PCI Express® Gen 4
Stream Processors	6144 Units
Core Clocks	Boost: Up to 2500 MHz Game: Up to 2300 MHz
Memoria	24GB GDDR6
Output	DisplayPort x3 (up to v2.1) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1)
Motor de gráficos	AMD Radeon™ RX 7900 XTX
Máximo de pantallas	4
FreeSync™ Technology	Y
Resolución máxima digital	7680x4320
Alimentación recomendada (W)	800W
Conectores de alimentación	8-pin x 3
Soporte OpenGL Versión	4.6

FEATURES



TRI FROZR 2

TRI FROZR 2 offers the perfect balance between cool temperatures and quiet fans during endless gaming sessions.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.




Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Mystic Light

Mystic Light gives you complete control of the RGB lighting for MSI devices and compatible RGB products.

Dimensiones (mm) 325 x 141 x 56 mm

CONNECTIONS

