


SPECIFICATIONS

Nazwa Modelu	GeForce RTX™ 3080 SUPRIM X 10G LHR
Pamięć	10GB GDDR6X
Silnik graficzny	NVIDIA® GeForce RTX™ 3080
Standard magistrali	PCI Express® Gen 4
Interfejs pamięci	320-bit
Taktowanie rdzenia GPU (MHz)	Extreme Performance: 1920 MHz (MSI Center) Boost: 1905 MHz (GAMING & SILENT Mode)
Prędkość pamięci	19 Gbps
Maks. liczba wyświetlaczy	4
Multi-GPU Technology	Y
Pobór mocy (W)	370W
Wyjścia	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz as specified in HDMI™ 2.1)
Obsługa HDCP	Y
Zalecany zasilacz (W)	850W
Virtual Reality Ready	Y
Maks. rozdzielczość cyfrowa	7680 x 4320
Złącza zasilania	8-pin x 3
Obsługa DirectX (wersja)	12 API
Obsługa OpenGL (wersja)	4.6
Wymiary karty (mm)	336 x 140 x 61 mm
Waga	1882g / 3178g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Close Quarters Heatpipe & Heatsink

Memory modules have their own close quarters heatpipe and heatsink for dedicated cooling.



Dual BIOS

Dual BIOS gives you the choice to prioritize for full performance in GAMING mode or low noise in SILENT mode.



TRI FROZR 2S

Thermals are kept in check in masterful ways under that sculpted exterior, letting you focus on your games.