




SPECIFICATIONS

Nazwa modelu	GeForce RTX™ 4070 Ti SUPRIM 12G
Pamięć	12GB GDDR6X
Silnik graficzny	NVIDIA® GeForce RTX™ 4070 Ti
Standard magistrali	PCI Express® Gen 4
Interfejs pamięci	192-bit
Taktowanie rdzenia GPU (MHz)	Extreme Performance: 2760 MHz (MSI Center) Boost: 2745 MHz (GAMING & SILENT Mode)
Prędkość pamięci	21 Gbps
Maks. liczba wyświetlaczy	4
Technologia G-SYNC®	Y
Obsługa HDCP	Y
Pobór mocy (W)	285 W
Wyjścia	DisplayPort x 3(v1.4a) HDMI™ x 1 (supports 4K 120Hz HDR and 8K 60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
Zalecany zasilacz (W)	750 W
Maks. rozdzielczość cyfrowa	7680x4320
Złącza zasilania	16-pin x 1
Obsługa DirectX (wersja)	12 Ultimate
Obsługa OpenGL (wersja)	4.6
Wymiary karty (mm)	338 x 142 x 73 mm
Waga	2019g / 3224g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Air Antegrade Fin

A section of V-shape heatsink and side-fins work to refocus air resistance at the passthrough.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.