



SPECIFICATIONS

Nazwa Modelu	GeForce RTX™ 4080 SUPER 16G GAMING X SLIM WHITE
Pamięć	16GB GDDR6X
Silnik graficzny	NVIDIA® GeForce RTX™ 4080 SUPER
Standard magistrali	PCI Express® Gen 4
Interfejs pamięci	256-bit
Taktowanie rdzenia GPU (MHz)	Extreme Performance: 2625 MHz (MSI Center) Boost: 2610 MHz (GAMING & SILENT Mode)
Prędkość pamięci	23 Gbps
Maks. liczba wyświetlaczy	4
Pobór mocy (W)	320 W
Obsługa HDCP	Y
Wyjścia	DisplayPort x 2 (v1.4a) HDMI™ x 2 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Maks. rozdzielczość cyfrowa	7680 x 4320
Zalecany zasilacz (W)	850 W (Min.750 W)
Złącza zasilania	16-pin x 1
Obsługa DirectX (wersja)	12 Ultimate
Obsługa OpenGL (wersja)	4.6
Wymiary karty (mm)	322 x 136 x 62 mm
Waga	1628g / 2494g (w/ mousepad), 2327(w/o mousepad)

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.