



SPECIFICATIONS

Nazwa marketingowa	GeForce RTX™ 5060 8G VENTUS 2X OC
Nazwa modelu	G5060-8V2C
Pamięć	8GB GDDR7
Silnik graficzny	NVIDIA® GeForce RTX™ 5060
Standard magistrali	PCI Express® Gen 5 x16 (uses x8)
Interfejs pamięci	128-bit
Taktowanie rdzenia GPU (MHz)	Extreme Performance: 2535 MHz (MSI Center) Boost: 2527 MHz
Prędkość pamięci	28 Gbps
Maks. liczba wyświetlaczy	4
Wyjścia	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Obsługa HDCP	Y
Pobór mocy (W)	145 W
Zalecany zasilacz (W)	550 W
Maks. rozdzielczość cyfrowa	7680 x 4320
Złącza zasilania	8-pin x1
Obsługa DirectX (wersja)	12 Ultimate
Obsługa OpenGL (wersja)	4.6
Wymiary karty (mm)	197 x 120 x 41 mm
Waga	511 g / 829 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.