



SPECIFICATIONS

Nazwa marketingowa	GeForce RTX™ 5080 16G VENTUS 3X OC PLUS
Nazwa modelu	G5080-16V3CP
Pamięć	16GB GDDR7
Silnik graficzny	NVIDIA® GeForce RTX™ 5080
Standard magistrali	PCI Express® Gen 5
Interfejs pamięci	256-bit
Taktowanie rdzenia GPU (MHz)	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz
Prędkość pamięci	30 Gbps
Maks. liczba wyświetlaczy	4
Wyjścia	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Obsługa HDCP	Y
Pobór mocy (W)	360 W
Zalecany zasilacz (W)	850 W
Maks. rozdzielczość cyfrowa	7680 x 4320
Złącza zasilania	16-pin x 1 (ATX 3.1 PSU recommended)
Obsługa DirectX (wersja)	12 Ultimate
Obsługa OpenGL (wersja)	4.6
Wymiary karty (mm)	303 x 121 x 49 mm
Waga	1105 g / 1618 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.