

GeForce RTX™ 4060 Ti GAMING 8G









SPECIFICATIONS

Memory	8GB GDDR6
Power connectors	8-pin x 1
Grafik Motoru	NVIDIA [®] GeForce RTX [™] 4060 Ti
Veriyolu Standardı	PCI Express [®] Gen 4 x16 (uses x8)
Bellek Arayüzü	128-bit
Çekirdek Hızı(MHz)	Extreme Performance: 2550 MHz (MSI Center) Boost: 2535 MHz
Bellek Hızı(MHz)	18 Gbps
Maximum Displays	4
Power consumption (W)	160 W
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
HDCP Desteği	Y
Digital Maximum Resolution	7680 x 4320
Recommended Power Supply (W)	550 W
DirectX Desteği	12 Ultimate
Boyutlar (mm)	247 x 130 x 42 mm
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·

CONNECTIONS

the U.S. and other countries



- 1. DisplayPort
- 2. HDMI™

FEATURES



TWIN FROZR 9

MSI's TWIN FROZR 9 thermal design enhances heat dissipation all around the graphics card.



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.