



SPECIFICATIONS

Memory	12GB GDDR6X
Power connectors	16-pin x 1
Grafik Motoru	NVIDIA® GeForce RTX™ 4070 Ti
Veriyolu Standardı	PCI Express® Gen 4
Bellek Arayüzü	192-bit
Çekirdek Hızı(MHz)	Extreme Performance: 2745 MHz (MSI Center) Boost: 2730 MHz
Bellek Hızı(MHz)	21 Gbps
Maximum Displays	4
Power consumption (W)	285 W
HDCP Desteği	Y
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
Recommended Power Supply (W)	700 W
Digital Maximum Resolution	7680 x 4320
DirectX Desteği	12 Ultimate
Boyutlar (mm)	307 x 125 x 51 mm

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.