




SPECIFICATIONS

Memory	24GB GDDR6X
Grafik Motoru	NVIDIA® GeForce RTX® 4090
Veriyolu Standardı	PCI Express® Gen 4
Bellek Arayüzü	384-bit
Çekirdek Hızı(MHz)	TBD
Bellek Hızı(MHz)	21 Gbps
Maximum Displays	4
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP Desteği	Y
Power consumption (W)	TBD
Recommended Power Supply (W)	850 W
Digital Maximum Resolution	7680x4320
DirectX Desteği	12 Ultimate
Boyutlar (mm)	337 x 140 x 77 mm

CONNECTIONS



FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Anti Bending

A die-cast anti-bending plate reinforces the card while thermal pads allow cooling to reach critical component underneath.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.