


## SPECIFICATIONS

Model Name	GeForce RTX™ 4080 SUPER 16G SUPRIM X
繪圖引擎	NVIDIA® GeForce RTX™ 4080 SUPER
科技介面	PCI Express® Gen 4
動態 / 核心時脈(MHz)	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz (GAMING & SILENT Mode)
Cores	10240 Units
記憶體速度	23 Gbps
Memory	16GB GDDR6X
記憶體介面	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP Support	Y
功耗(W)	320 W
供電接口	16-pin x 1
建議電源供應(W)	850 W (Min.750 W)
顯示卡尺寸(mm)	336 x 142 x 78 mm
重量 (顯示卡 / 包裝盒)	2372g / 3573g
DirectX 支援版本	12 Ultimate
OpenGL 支援版本	4.6
最大螢幕輸出數量	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

## CONNECTIONS



1. DisplayPort
2. HDMI™

## FEATURES



### TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.




### TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



### Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



### Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



### Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



### Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



### Aluminum Backplate

Thermal pads beneath the sturdy metal backplate provide additional cooling.



### Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.