



SPECIFICATIONS

Model Name	G506T-16V3C
繪圖引擎	NVIDIA® GeForce RTX™ 5060 Ti
科技介面	PCI Express® Gen 5 x16 (uses x8)
動態 / 核心時脈(MHz)	Extreme Performance: 2617 MHz (MSI Center) Boost: 2602 MHz
Cores	4608 Units
記憶體速度	28 Gbps
Memory	16GB GDDR7
記憶體介面	128-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
功耗(W)	180 W
供電接口	8-pin x 1
建議電源供應(W)	600 W
顯示卡尺寸(mm)	304 x 121 x 44 mm
重量 (顯示卡 / 包裝盒)	860 g / 1229 g
DirectX 支援版本	12 Ultimate
OpenGL 支援版本	4.6
最大螢幕輸出數量	4
G-SYNC® technology	Y
Marketing Name	GeForce RTX™ 5060 Ti 16G VENTUS 3X OC
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Triple Fan



Three fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 5.0



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Solid Baseplate



A solid baseplate transfers heat from the GPU to all heat pipes for better cooling.

Metal Backplate



A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.

Zero Frozr



Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.

DrMOS



DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

Fuse



Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.