



SPECIFICATIONS

Model Name	G5070-12V2
繪圖引擎	NVIDIA® GeForce RTX™ 5070
科技介面	PCI Express® Gen 5
動態 / 核心時脈(MHz)	Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz
Cores	6144 Units
記憶體速度	28 Gbps
Memory	12GB GDDR7
記憶體介面	192-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
功耗(W)	250 W
供電接口	16-pin x 1 (ATX 3.1 PSU recommended)
建議電源供應(W)	650 W
顯示卡尺寸(mm)	236 x 126 x 50 mm
重量 (顯示卡 / 包裝盒)	774 g / 1149 g
DirectX 支援版本	12 Ultimate
OpenGL 支援版本	4.6
最大螢幕輸出數量	4
G-SYNC® technology	Y
Marketing Name	GeForce RTX™ 5070 12G VENTUS 2X
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



FEATURES

- Dual Fan**
Two fans and a huge heatsink ensure a cool and quiet experience for you.
- TORX FAN 5.0**
Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.
- Nickel-plated Copper Baseplate**
Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.
- Core Pipes**
Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.
- Metal Backplate**
A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.
- Zero Frozr**
Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.
- DrMOS**
DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.
- Fuse**
Additional fuses built into the custom PCB provide additional safeguards against electrical damage.
- MSI Center**
The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.
- Afterburner**
Take full control with the most recognized and widely used graphics card overclocking software in the world.