



## SPECIFICATIONS

Model Name	G5090-32SPS
繪圖引擎	NVIDIA® GeForce RTX™ 5090
科技介面	PCI Express® Gen 5 x16
動態 / 核心時脈(MHz)	Gaming Mode: Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz
	Silent Mode: Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz
Cores	21760 Units
記憶體速度	28 Gbps
Memory	32GB GDDR7
記憶體介面	512-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
功耗(W)	Gaming mode: 600 W Silent mode: 575 W
供電接口	16-pin x 1 (ATX 3.1 PSU recommended)
建議電源供應(W)	1000 W
顯示卡尺寸(mm)	359 x 150 x 76 mm
重量 (顯示卡 / 包裝盒)	2840 g / 3695 g
DirectX 支援版本	12 Ultimate
OpenGL 支援版本	4.6
最大螢幕輸出數量	4
G-SYNC® technology	Y
Marketing Name	GeForce RTX™ 5090 32G SUPRIM SOC
Digital Maximum Resolution	7680 x 4320

## CONNECTIONS

## FEATURES




### HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



### STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.




### Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.




### Optimized Heat Distribution - Core Pipe

Square-shaped Core Pipes maximize heat dissipation with the Vapor Chamber for superior cooling.



### Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



### Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.




### Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



### MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



1. DisplayPort
2. HDMI™