

## SPECIFICATIONS

<b>Ядра</b>	7168 Units
<b>Пам'ять</b>	12GB GDDR6X
<b>Коннектори живлення</b>	16-pin x 1
<b>Габарити відеокарти (мм)</b>	307 x 125 x 46 mm
<b>Графічний процесор</b>	NVIDIA® GeForce RTX™ 4070 SUPER
<b>Стандарт підключення</b>	PCI Express® Gen 4
<b>Розрядність шини пам'яті</b>	192-bit
<b>Тактова частота ядра</b>	Extreme Performance: 2490 MHz (MSI Center) Boost: 2475 MHz
<b>Максимальна кількість дисплеїв для підключення</b>	4
<b>Тактова частота пам'яті</b>	21 Gbps
<b>Енергоспоживання</b>	220 W
<b>Рекомендована потужність блоку живлення</b>	650 W
<b>Підтримка HDCP</b>	Y
<b>Конектори</b>	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
<b>Максимальна цифрова роздільна здатність</b>	7680 x 4320
<b>Підтримка версії DirectX</b>	12 Ultimate
<b>Вага</b>	972g / 1585 g

## CONNECTIONS



1. DisplayPort
2. HDMI™

## FEATURES



### TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



### TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



### Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.




### Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



### Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



### Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



### Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



### MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.