



SPECIFICATIONS

| | |
|---|--|
| Ядра | 7680 Units |
| Пам'ять | 12GB GDDR6X |
| Коннектори живлення | 16-pin x 1 |
| Габарити відеокарти (мм) | 307 x 125 x 51 mm |
| Графічний процесор | NVIDIA® GeForce RTX™ 4070 Ti |
| Стандарт підключення | PCI Express® Gen 4 |
| Розрядність шини пам'яті | 192-bit |
| Тактова частота ядра | Extreme Performance: 2625 MHz (MSI Center) Boost: 2610 MHz |
| Максимальна кількість дисплеїв для підключення | 4 |
| Тактова частота пам'яті | 21 Gbps |
| Енергоспоживання | 285 W |
| Рекомендована потужність блоку живлення | 700 W |
| Коннектори | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI 2.1a) |
| Підтримка HDCP | Y |
| Максимальна цифрова роздільна здатність | 7680 x 4320 |
| Підтримка версії DirectX | 12 Ultimate |
| Вага | 1086 g / 1843 g |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.