


SPECIFICATIONS

Ядра	10240 Units
Пам'ять	16GB GDDR6X
Коннектори живлення	16-pin x 1
Габарити відеокарти (мм)	336 x 142 x 78 mm
Графічний процесор	NVIDIA® GeForce RTX™ 4080 SUPER
Стандарт підключення	PCI Express® Gen 4
Розрядність шини пам'яті	256-bit
Тактова частота ядра	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz (GAMING & SILENT Mode)
Максимальна кількість дисплеїв для підключення	4
Тактова частота пам'яті	23 Gbps
Енергоспоживання	320 W
Рекомендована потужність блоку живлення	850 W (Min.750 W)
Підтримка HDCP	Y
Конектори	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Максимальна цифрова роздільна здатність	7680 x 4320
Підтримка версії DirectX	12 Ultimate
Вага	2372g / 3573g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.




Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.