

SPECIFICATIONS

Назва	GeForce RTX™ 5060 Ti 8G GAMING TRIO
Ядра	4608 Units
Пам'ять	8GB GDDR7
Конектори живлення	16-pin x 1
Графічний процесор	NVIDIA® GeForce RTX™ 5060 Ti
Стандарт підключення	PCI Express® Gen 5 x16 (uses x8)
Габарити відеокарти (мм)	300 x 125 x 44 mm
Розрядність шини пам'яті	128-bit
Тактова частота ядра	Extreme Performance: 2587 MHz (MSI Center) Boost: 2572 MHz
Підтримка версії OpenGL	4.6
Тактова частота пам'яті	28 Gbps
Максимальна кількість дисплеїв для підключення	4
Енергоспоживання	180 W
Рекомендована потужність блоку живлення	600 W
Конектори	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Підтримка HDCP	Y
Максимальна цифрова роздільна здатність	7680 x 4320
Підтримка версії DirectX	12 Ultimate
Вага	839 g / 1345 g

CONNECTIONS

FEATURES



TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



1. DisplayPort
2. HDMI™