

SPECIFICATIONS

Назва	GeForce RTX™ 5070 12G GAMING TRIO
Ядра	6144 Units
Пам'ять	12GB GDDR7
Конектори живлення	16-pin x 1
Графічний процесор	NVIDIA® GeForce RTX™ 5070
Стандарт підключення	PCI Express® Gen 5
Габарити відеокарти (мм)	338 x 140 x 50 mm
Розрядність шини пам'яті	192-bit
Тактова частота ядра	Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz
Підтримка версії OpenGL	4.6
Тактова частота пам'яті	28 Gbps
Максимальна кількість дисплеїв для підключення	4
Енергоспоживання	250 W
Рекомендована потужність блоку живлення	650 W
Конектори	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Підтримка HDCP	Y
Максимальна цифрова роздільна здатність	7680 x 4320
Підтримка версії DirectX	12 Ultimate
Вага	1187 g / 1705 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.