




SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 Ti 16G GAMING OC
Model Name	G506T-16GC
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060 Ti
Cores	4608 Units
Memory	16GB GDDR7
Power connectors	16-pin x 1 (ATX 3.1 PSU recommended)
Bus Standard	PCI Express® Gen 5 x16 (uses x8)
Memory Interface	128-bit
Core Clocks	Extreme Performance: 2662 MHz (MSI Center) Boost: 2647 MHz
Memory Speed	28 Gbps
Maximum Displays	4
Digital Maximum Resolution	7680 x 4320
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption (W)	180 W
Recommended Power Supply (W)	600 W
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Card Dimension(mm)	247 x 135 x 51 mm
Weight	781 g / 1181 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Twin Frozr 10



Experience superior cooling and quieter performance with MSI's enhanced fan blade design.

STORMFORCE FAN




Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.

Nickel-plated Copper Baseplate



Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.

Core Pipes




Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.

Metal Backplate




A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.

Wave Curved 4.0



Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.

Air Antegrade Fin 2.0



The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.