



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5090 32G SUPRIM LIQUID SOC
Model Name	G5090-32SLS
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5090
Cores	21760 Units
Memory	32GB GDDR7
Power connectors	16-pin x 1 (ATX 3.1 PSU recommended)
Bus Standard	PCI Express® Gen 5x 16
Memory Interface	512-bit
Core Clocks	Gaming Mode: Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz Silent Mode: Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz
Memory Speed	28 Gbps
Maximum Displays	4
Digital Maximum Resolution	7680 x 4320
Output	DisplayPort x 3 (2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption (W)	Gaming mode: 600 W Silent mode: 575 W
Recommended Power Supply (W)	1000 W
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Card Dimension(mm)	Card: 280 x 148 x 51mm Radiator: 394 x 121 x 55mm Tube length: 450mm
Weight	2969 g / 4273 g


CONNECTIONS

FEATURES



SUPERIOR HYBRID COOLING

SUPRIM LIQUID's innovative Hybrid design uses both air cooling with STORMFORCE Fan and liquid cooling to effectively manage heat from the GPU and VRAM.



Advanced Performance Pump

A premium design for optimal flow, delivering automotive-grade coolant to ensure the SUPRIM LIQUID stays cool and performs efficiently.



Patented Water Block Design

The patented water block features a special waterway layout and CNC-machined copper base that cools the GPU and VRAM, helping to lower temperatures.



360 mm Aluminum Radiator

The 360 mm aluminum radiator ensures efficient cooling, while the STORMFORCE fans enhance airflow and simplifies cable management for a tidy installation.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Micro-Fin Copper Base

A copper base with fine micro-fins immersed in the liquid stream effectively transfers heat away from the VRAM and GPU.



Durable Tubing with Scratch-proof Cover

Braided PVC tubes resist permeation and stay flexible, while the scratch-proof cover enhances durability during SUPRIM LIQUID installation.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.




MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



GRAPHICS CARDS

GeForce RTX™ 5090 32G SUPRIM LIQUID SOC



1. DisplayPort
2. HDMI™