



SPECIFICATIONS

| | |
|-----------------------------------|---|
| Marketing Name | GeForce RTX™ 5060 Ti 16G VANGUARD OC |
| Model Name | G506T-16VGC |
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 5060 Ti |
| Interface | PCI Express® Gen 5 x16 (uses x8) |
| Core Clocks | Extreme Performance: 2662 MHz (MSI Center) Boost: 2647 MHz |
| Cores | 4608 Units |
| Memory Speed | 28 Gbps |
| Memory | 16GB GDDR7 |
| Memory Bus | 128-bit |
| Output | DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| HDCP Support | Y |
| Power consumption | 180W |
| Power Connectors | 16-pin x 1 (ATX 3.1 PSU recommended) |
| Recommended PSU (W) | 600 W |
| Card Dimension(mm) | 337 x 140 x 61 mm |
| Weight (Card / Package) | 1278 g / 2059 g |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| G-SYNC™ technology | Y |
| Digital Maximum Resolution | 7680 x 4320 |

FEATURES



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.

CONNECTIONS



1. DisplayPort
2. HDMI™