



## SPECIFICATIONS

Marketing Name	GeForce RTX™ 5090 32G SUPRIM SOC
Model Name	G5090-32SPS
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5090
Interface	PCI Express® Gen 5 x16
Core Clocks	 Gaming Mode: Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz
Cores	21760 Units
Memory Speed	28 Gbps
Memory	32GB GDDR7
Memory Bus	512-bit
Output	 DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	 Gaming mode: 600 W Silent mode: 575 W
Power Connectors	16-pin x 1 (ATX 3.1 PSU recommended)
Recommended PSU (W)	1000 W
Card Dimension(mm)	359 x 150 x 76 mm
Weight (Card / Package)	2840 g / 3695 g
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC™ technology	Y
Digital Maximum Resolution	7680 x 4320

## CONNECTIONS

## FEATURES

### HYPER FROZR THERMAL DESIGN




An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.

### STORMFORCE FAN




Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.

### Advanced Vapor Chamber




Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.

### Optimized Heat Distribution - Core Pipe




Square-shaped Core Pipes maximize heat dissipation with the Vapor Chamber for superior cooling.

### Wave Curved 4.0



Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.

### Air Antegrade Fin 2.0



The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.

### Metal Backplate




A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.

### MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



1. DisplayPort
2. HDMI™