




SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G VENTUS 3X
Memory	8GB GDDR7
Vi xử lý đồ họa	NVIDIA® GeForce RTX™ 5060
Chuẩn giao tiếp	PCI Express® Gen 5 X16 (uses x8)
Bus bộ nhớ	128-bit
Xung nhịp nhân đồ họa(MHz)	Extreme Performance: 2512 MHz (MSI Center) Boost: 2497 MHz
Xung nhịp bộ nhớ (MHz)	28 Gbps
Hỗ trợ màn hình tối đa	4
G-SYNC™ technology	Y
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Hỗ trợ HDCP	Y
Công suất tiêu thụ (W)	145 W
Công suất nguồn đề nghị (W)	TBD
Digital Maximum Resolution	7680 x 4320
Nguồn phụ	8-pin x1
Hỗ trợ phiên bản DirectX	12 Ultimate
Hỗ trợ phiên bản OpenGL	4.6
Kích thước (mm)	303 x 121 x 41 mm
Cân nặng	684 g / 1042 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.