

Modem Card

System Configuration				
MB Barcode		R114 6B20354792		
Device Configuration		Manufacturer	Model No.	
		Spec.		
	Processor	<i>Intel</i>	<i>Pentium4 3.2GHZ(Prescott)</i>	<i>FSB800MHZ</i>
	Memory	<i>A-DATA</i>	<i>Vitesta M2OEL6F3G3160A1E0Z</i>	<i>256MB,PC2 6400</i>
	VGA Card	<i>MSI</i>	<i>MS-8997 (Radeon X800 Pro)</i>	<i>PCI-E X16,128MB</i>
	Lan Card	<i>Realtek</i>	<i>RTL8111B</i>	
	Sound Card	<i>Realtek</i>	<i>ALC888</i>	<i>AC"97</i>
	Hard Drive	<i>HITACHI</i>	<i>HDS728080PLA380</i>	<i>80GB</i>
	CD-ROM	<i>MSI</i>	<i>MS-8216B-010</i>	<i>16X DVDROM,ATA33</i>
	Floppy Drive	<i>SAMSUNG</i>	<i>SFD-321B</i>	<i>1.44MB</i>
	Power Supply	<i>Thermaltake</i>	<i>PurePower</i>	<i>460W</i>
	Mouse	<i>多彩</i>	<i>M346</i>	<i>PS/2</i>
	Keyboard	<i>MSI</i>	<i>MSI-101XBL</i>	<i>PS/2</i>
Monitor	<i>BENQ</i>	<i>A770Plus</i>	<i>17"CRT</i>	
SW Info	VGA BIOS	<i>Intel Video Bios</i>		
	VGA Driver	<i>6.14.10.4421</i>	<i>As Follows</i>	
	MB Driver		<i>(from MI31009-CD)</i>	

Model		Spec.	Result
ALPHA net	AF56K(ESS ES2838S)	PCI ; 56K	OK