

Be Your Window To The World



Picture and logos

SELLING POINTS

- 1500R curvature brings the most immersive viewing experience for your work & amusement.
- TÜV certified display protects your eyesight and keeps your eyes healthy
- Anti-Flicker and Less Blue Light technologies prevent your eyes from strain & fatigue
- Ergonomic software, Display Kit, provides the most convenient tool, the proper color & display mode to you while working with it everyday
- 75 Hz refresh rate provides a better viewing experience
- Keep the flexibility for your different devices with multiple input sources: HDMI™ & D-Sub (VGA) ports
- Standard VESA mountable design
- Always allow you to join an online conference call with built-in speakers



1. 1x DC Jack
2. 1x HDMI™ (1.4b)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x Headphone-out
6. 1x Kensington Lock
7. 1x 5-Way Navigator

SPECIFICATION

Barcode Info	EAN	4711377002172
	UPC	824142298190
	UCC14	10824142298197
Model	Part No	9S6-3PB3CM-011
	MKT Name	PRO MP272C
	MKT Spec	PRO MP272C
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	598(H) x 336(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~90 KHz(H) / 48~75 Hz(V)
	Refresh Rate	75Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	5ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	85%/75%
	NTSC (CIE1931 area percentage/overlap)	72%/70%
	sRGB (CIE1976 area percentage/overlap)	98%/95%
	sRGB (CIE1931 area percentage/overlap)	99%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	83%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	75%/73%
	DCI-P3 (CIE1976 area percentage/overlap)	77%/77%
	DCI-P3 (CIE1931 area percentage/overlap)	74%/74%
	Rec.709 (CIE1976 area percentage/overlap)	98%/95%
	Rec.709 (CIE1931 area percentage/overlap)	99%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	56%/56%
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%
	Display Colors	16.7M
	Color bit	8 bits
	Note_HDMI™	1920 x 1080 (Up to 75Hz)
Note_DVI	N/A	
I/O Ports	Line-in	1
	HDMI™	1
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	D-Sub	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2
Power	Power Type	External Adaptor 12V 4A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	F
	Adapter's KC safety Number	HU101009-20006A
	Power Cord Type	C13

In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	4
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
Quick Guide	1	
Pallet	pcs/Carton	N/A
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	858 x 150 x 491
	Outer Carton Dimension (WxDxH) (inch)	33.78 x 5.91 x 19.33
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	610.5 x 250 x 462.5
	Product Dimension with Stand (WxDxH) (inch)	24.04 x 9.84 x 18.21
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	610.5 x 84.3 x 362.5
	Product Dimension without Stand (WxDxH) (inch)	24.04 x 3.32 x 14.27
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	250 x 250 x 347.4
	Stand Dimension (WxDxH) (inch)	9.84 x 9.84 x 13.68
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	840 x 132 x 458
	Inside Carton Dimension (WxDxH) (inch)	33.07 x 5.2 x 18.03
	Weight (Net kg)	5
	Weight (Gross kg)	7.03
Weight	Weight Without Stand (kg)	3.32
Warranty	Warranty	12M