

Be Your Window To The World



Picture and logos

SELLING POINTS

- Perfect 27" screen size for the programming, coding & website design workspace.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker and Less Blue Light technology helps prevent eye strain and fatigue.
- 100Hz refresh rate provides a better viewing experience with flicker-free image.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- The stand is designed with ergonomic features, including tilt, swivel, height, and pivot adjustments.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and DisplayPort ports.
- Standard VESA mountable design.
- Two built-in speakers.
- A sustainable solution for protecting the environment.



1. 5-way Navigator
2. 1x AC-in
3. 1x HDMI™ 2.0b (WQHD@100Hz)
4. 1x DisplayPort
5. 1x HDMI™ 2.0b (WQHD@100Hz)
6. 1x Headphone-out
7. 1x Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PC39M-071
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	71.04~186.3 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/81%
	NTSC (CIE1931 area percentage/overlap)	74%/72%
	sRGB (CIE1976 area percentage/overlap)	100%/95%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/84%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	100%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614 x 226.9 x 562.6
	Product Dimension without Stand (WxDxH) (mm)	614 x 55.9 x 361.1
	Stand Dimension (WxDxH) (mm)	259.7 x 226.9 x 411.5
	Weight (Net kg)	6.26
	Weight Without Stand (kg)	3.66
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	83.1 x 13.3 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	85 x 15 x 48
	Weight (Gross kg)	9.32
Barcode Info	EAN	4711377287258