



MONITOR

MAG 273QP QD-OLED X24

MAG 273QP QD-OLED X24

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- 3rd Gen QD-OLED Panel - With stunning image quality and fast response time.
- Fastest 0.03ms GtG response time and 240Hz refresh rate.
- QD Premium Color - Ensures the color meets the market standard - Delta E $\leq$ 2.
- Incredible HDR visual - VESA DisplayHDR True Black 400.
- MSI OLED Care 2.0 - Reduced the risk of OLED image sticking / burn-in.
- 3-Year Burn-In Warranty - Including coverage for OLED burn-in.



1. DC-in
2. Headphone-out
3. 5-way Joystick Navigator
4. 2x HDMI™ 2.1a (WQHD@240Hz)
5. DisplayPort 1.4a (HBR3)
6. Kensington Lock



MONITOR

MAG 273QP QD-OLED X24

MAG 273QP QD-OLED X24

SPECIFICATION

Model	Part No	9S6-3CE69H-004
	Color	ID1/Black-Black
Display	Screen Size	26.5" (67.31 cm)
	Active Display Area (mm)	590.42(H) x 333.72(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2292(H)x0.2292(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	NVIDIA G-SYNC Compatible / AMD FreeSync™ Premium Pro
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	VESA DisplayHDR True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	96.24~265.98 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.7%/94.4%
	NTSC (CIE1931 area percentage/overlap)	104.3%/92.4%
	sRGB (CIE1976 area percentage/overlap)	138.4%/100%
	sRGB (CIE1931 area percentage/overlap)	147.6%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.6%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109.4%/94.9%
	DCI-P3 (CIE1976 area percentage/overlap)	110.2%/99.1%
	DCI-P3 (CIE1931 area percentage/overlap)	108.8%/98.5%
	Rec.709 (CIE1976 area percentage/overlap)	138.4%/100%
	Rec.709 (CIE1931 area percentage/overlap)	147.6%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.3%/80.3%
	Rec.2020 (CIE1931 area percentage/overlap)	78.1%/78.1%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
	Color bit	10 bits
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1 (FRL 6G)
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
	Warranty	36M
Power	Power Type	External Adaptor 24V 5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	25
	Annual Energy Consumption (KWh)	25
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C5



MONITOR

MAG 273QP QD-OLED X24

MAG 273QP QD-OLED X24

Accessories	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	610.11 x 227.9 x 532.01
	Product Dimension without Stand (WxDxH) (mm)	610.11 x 54.5 x 358.23
	Stand Dimension (WxDxH) (mm)	308.61 x 227.9 x 412.58
	Weight (Net kg)	6.7
	Weight Without Stand (kg)	4.05
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	78 x 14 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	79.5 x 15.3 x 49.9
	Weight (Gross kg)	9.65
Barcode Info	EAN	4711377281720