



MONITOR
MAG 325CQF
MAG 325CQF

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Rapid VA Panel – Provides 0.5ms (GtG, Min.) response time, optimizes screen colors and brightness.
- 180Hz Refresh Rate – Respond faster with smoother frames.
- 0.5ms (GtG, Min.) Response Time – Eliminate screen tearing and choppy frame rates.
- AI Vision – The new AI Vision technology can not only reveal details in dark areas but also enhance overall brightness and saturate colors.
- Less Blue Light – Use a software solution to reduce the light emission in the blue-violet region of the blue light spectrum.



1. 5-Way Navigator
2. DC-in
3. Headphone-out
4. DisplayPort 1.4a
5. 2x HDMI™ 2.0b (WQHD@144Hz)
6. Type-C
7. Kensington Lock



MONITOR
MAG 325CQF
MAG 325CQF

SPECIFICATION

Model	Part No	9S6-3DC11H-078
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80.01 cm)
	Active Display Area (mm)	697.344 (H) x 392.256 (V)
	Curvature	Curve 1000R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2724(H)x0.2724(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	90.90~248.25 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	108%/87%
	NTSC (CIE1931 area percentage/overlap)	90%/82%
	sRGB (CIE1976 area percentage/overlap)	124%/99%
	sRGB (CIE1931 area percentage/overlap)	128%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	106%/91%
	Adobe RGB (CIE1931 area percentage/overlap)	95%/86%
	DCI-P3 (CIE1976 area percentage/overlap)	99%/96%
	DCI-P3 (CIE1931 area percentage/overlap)	94%/92%
	Rec.709 (CIE1976 area percentage/overlap)	124%/99%
	Rec.709 (CIE1931 area percentage/overlap)	128%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/72%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 19V 4.74A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	32
	Annual Energy Consumption (KWh)	32
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C5



MONITOR
MAG 325CQF
MAG 325CQF

Accessories	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	704.62 x 269.46 x 502.85
	Product Dimension without Stand (WxDxH) (mm)	704.62 x 143.45 x 422.35
	Stand Dimension (WxDxH) (mm)	379.66 x 269.46 x 142.52
	Weight (Net kg)	6.4
	Weight Without Stand (kg)	5.65
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	80.8 x 19.6 x 51.6
	Outer Carton Dimension (WxDxH) (cm)	82.3 x 21.1 x 54
	Weight (Gross kg)	8.6
Barcode Info	EAN	4711377231190