

All About Gaming



Picture and logos

SELLING POINTS

- Rapid IPS - Provides 1ms GTG fast response time, optimizes screen colors and brightness.
- 180Hz Refresh Rate - Respond faster with smoother frames.
- 1ms GTG Response Time - Eliminate screen tearing and choppy frame rates.
- Wide Color Gamut - Game colors and details will look more realistic and refined.
- Adaptive-sync - Prevent screen tearing or stuttering, producing ultra-smooth lag-free gameplay.
- Night Vision - Smart black tuner to brighten your day by bringing out the fine details in dark areas.
- Frameless design - Enjoy the ultimate gaming experience with super narrow bezels.
- Anti-Flicker and Less Blue Light - Game even longer and prevent eye strain and fatigue.
- 178° Wide Viewing Angle - Colors and details will stay sharp at more angles with a 178° wide viewing angle.



1. 5-way joystick navigator
2. DC-in
3. 1 x Display Port (1.4)
4. 2 x HDMI™ (2.0b)
5. Headphone out
6. Kensington lock

SPECIFICATION

Model	SKU Number	9S6-3CD39T-025
	Entity MKT Name	G272QPF E2
	Part No	9S6-3CD39T-025
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1200:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	64.56~266.4 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	109%/86%
	NTSC (CIE1931 area percentage/overlap)	90%/82%
	sRGB (CIE1976 area percentage/overlap)	125%/99%
	sRGB (CIE1931 area percentage/overlap)	127%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	107%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	94%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	99%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	94%/92%
	Rec.709 (CIE1976 area percentage/overlap)	125%/99%
	Rec.709 (CIE1931 area percentage/overlap)	127%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/71%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
Display Colors	1.07B	
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613 x 228 x 409
	Product Dimension without Stand (WxDxH) (mm)	613 x 61 x 369
	Stand Dimension (WxDxH) (mm)	309 x 228 x 391
	Weight (Net kg)	6.3
	Weight Without Stand (kg)	3.8
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	84 x 15 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	85.5 x 16.5 x 50
	Weight (Gross kg)	8.4
Barcode Info	EAN	4711377141765