

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Perfect 23.8" screen size for the programming, coding & website design workspace
- TÜV certified anti-flicker, less blue light display protects your eyesight and keeps your eyes healthy
- 100 Hz refresh rate & 1ms (MPRT) response time provides a better viewing experience
- Check if your eyes have to take a nap with Eye-Q check function
- Ergonomic software, Display Kit, provides the most convenient tool, the proper color & display mode to you while working with it everyday
- Enjoy the vivid brightness and darkness with a 4000:1 contrast ratio
- Keep the flexibility for your different devices with multiple input sources: HDMI™ port and D-Sub(VGA) port
- Assemble and disassemble the device with tool-free design
- Standard VESA mountable design



1. DC-in
2. 1x HDMI (1.4b)
3. 1x D-Sub (VGA)
4. 1x Headphone-out
5. Kensington Lock

SPECIFICATION

I/O Ports (Rear)	Card Reader	N/A
Power	Power Type	External Adaptor 12V 2.5A
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (inch)	N/A
	Weight (Net kg)	N/A
	Weight (Gross kg)	N/A
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension with Stand (WxDxH) (inch)	N/A
Weight	Weight Without Stand (kg)	N/A
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	N/A
Warranty	Warranty	24M
In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
Quick Guide	1	
Barcode Info	EAN	4711377121965
Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	527(H) x 296 (V)
	Curvature	Flat
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	HDR (High dynamic range)	N/A
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
Rec.2020 (CIE1931 area percentage/overlap)	N/A	
Display Colors	16.7M	
Color bit	8 bits	
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A



B U S I N E S S P R O D U C T I V I T Y M O N I T O R

PRO MP245V

PRO MP245V

Model	Part No	9S6-3PC0CM-002
	MKT Name	PRO MP245V
	MKT Spec	PRO MP245V
	Color	ID1/Black-Black
	Model	3PC0