

PATH TO THE FUTURE

Wir stellen vor: den MSI MAG 242FDE Esports-Gaming-Monitor. Dieser hochmoderne Monitor verfügt über ein 24-Zoll-FHD-Display mit einer blitzschnellen Bildwiederholungsrate von 200 Hz und einer schnellen MPRT-Reaktionszeit von 0,5 ms (GtG, Min.). Mit dem MAG 242F hast du den nötigen Wettbewerbsvorteil, um deine Gegner in Gaming-Schlachten zu übertreffen und zu besiegen.



Picture and logos

SELLING POINTS

- Rapid IPS Panel – Bietet eine Reaktionszeit von 0,5 ms (GtG, Min.), optimiert Bildschirmfarben und -helligkeit.
- 200 Hz Bildwiederholungsrate – Reagiert schneller mit flüssigeren Bildern.
- 0,5 ms (GtG, Min.) Reaktionszeit – Beseitigt Bildschirrmisse und abgehackte Bildraten.
- AI Vision – Die neue AI Vision Technik kann nicht nur Details in dunklen Bereichen sichtbar machen, sondern auch die Gesamthelligkeit verbessern und Farben sättigen.
- Less Blue Light – Verwendet eine Softwarelösung, um die Lichtemission im blau-violetten Bereich des blauen Lichtspektrums zu reduzieren.



1. 5-Wege Joystick Navigation
2. Stromanschluss
3. HDMI™ 2.0b (FHD@200Hz)
4. DisplayPort 1.2a (HBR2)
5. Kopfhörerausgang
6. Kensington lock

SPECIFICATION

Model	SKU Number	9S6-3BC51T-001
	Entity MKT Name	MAG 242F
	Part No	9S6-3BC51T-001
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~230 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/80%
	NTSC (CIE1931 area percentage/overlap)	79%/73%
	sRGB (CIE1976 area percentage/overlap)	115%/98%
	sRGB (CIE1931 area percentage/overlap)	112%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	99%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	83%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	92%/89%
	DCI-P3 (CIE1931 area percentage/overlap)	83%/82%
	Rec.709 (CIE1976 area percentage/overlap)	115%/98%
	Rec.709 (CIE1931 area percentage/overlap)	112%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	67%/67%
	Rec.2020 (CIE1931 area percentage/overlap)	59%/59%
	Surface Treatment	Anti-glare
Display Colors	1.07B	
Color bit	10 bits (8 bits + FRC)	
Schnittstellen	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18 (SDR) 30 (HDR)
	Annual Energy Consumption (KWh)	27
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
Power Cord Type	C13	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	540.2 x 220.1 x 396.8
	Product Dimension without Stand (WxDxH) (mm)	540.2 x 52.7 x 322
	Stand Dimension (WxDxH) (mm)	318 x 220.1 x 140
	Weight (Net kg)	3.
	Weight Without Stand (kg)	2.6
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.3 x 41
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 13.8 x 43.3
	Weight (Gross kg)	4.8
Barcode Info	EAN	4711377289795