

PATH TO THE FUTURE


Visualisiere deinen Sieg mit dem MAG 271QPXDE QD-OLED E2 Gaming-Monitor. Das 2560 x 1440 (WQHD) QD-OLED-Panel bietet eine Bildwiederholrate von 240 Hz und eine schnelle Reaktionszeit von 0,03 ms (GtG). Die VESA-Zertifizierung für ClearMR 13000 und DisplayHDR True Black 400 sorgt für außergewöhnlich lebendige Bilder und reduziert Bewegungsunschärfen. OLED Care 2.0 reduziert das Risiko des Einbrennen. Für Konsolenspieler bietet der MAG 271QPX QD-OLED E2 HDMI 2.1 Anschlüsse mit 48Gbps Bandbreite, 120Hz, VRR und ALLM Unterstützung.



Picture and logos

SELLING POINTS

- QD-OLED Panel der dritten Generation – Bietet beeindruckende Bildqualität und schnelle Reaktionszeiten.
- Schnellste 0,03 ms GtG-Reaktionszeit und 240 Hz Bildwiederholrate.
- QD Premium Color – Stellt sicher, dass die Farbgenauigkeit dem Marktstandard entspricht – Delta E ≤ 2.
- Unglaubliche HDR-Visuals – VESA DisplayHDR True Black 400.
- MSI OLED Care 2.0 – Verringert das Risiko von OLED-Einbrennen.
- Konsolenmodus – Bietet HDMI™ 2.1 (WQHD@240Hz) mit voller 48 Gbps Bandbreite.
- 3-Jahres-Garantie gegen Einbrennen – Einschließlich Abdeckung für OLED-Einbrennschäden.



1. Stromanschluss
2. 5-Wege Joystick Navigation
3. 2 x HDMI™ 2.1
4. Display Port (1.4a)
5. USB Typ-C (PD 15W)
6. Kopfhörerausgang
7. Kensington lock



MONITOR

MAG 271QPXDE QD-OLED E2

MAG 271QPX QD-OLED E2

SPECIFICATION

Model	Part No	9S6-3CD89T-038
	Color	ID1/Black-Black
Display	Screen Size	26.5" (67.31 cm)
	Active Display Area (mm)	590.42(H) x 333.72(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2292(H)x0.2292(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	30~390 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.7%/94.4%
	NTSC (CIE1931 area percentage/overlap)	104.3%/92.4%
	sRGB (CIE1976 area percentage/overlap)	138.4%/100%
	sRGB (CIE1931 area percentage/overlap)	147.6%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.6%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109.4%/94.9%
	DCI-P3 (CIE1976 area percentage/overlap)	110.2%/99.1%
	DCI-P3 (CIE1931 area percentage/overlap)	108.8%/98.5%
	Rec.709 (CIE1976 area percentage/overlap)	138.4%/100%
	Rec.709 (CIE1931 area percentage/overlap)	147.6%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.3%/80.3%
	Rec.2020 (CIE1931 area percentage/overlap)	78.1%/78.1%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
	Color bit	10 bits
Schnittstellen	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	40
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	G
	Power Cord Type	C13



M O N I T O R

MAG 271QPXDE QD-OLED E2

M A G 2 7 1 Q P X Q D - O L E D E 2

Zubehör	DisplayPort Cable	1
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	609 x 242 x 416
	Product Dimension without Stand (WxDxH) (mm)	609 x 72 x 362
	Stand Dimension (WxDxH) (mm)	309 x 242 x 391
	Weight (Net kg)	8.
	Weight Without Stand (kg)	5.3
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	80 x 18.5 x 50
	Outer Carton Dimension (WxDxH) (cm)	81.8 x 20 x 52.5
	Weight (Gross kg)	10.4
Barcode Info	EAN	4711377331180