

PATH TO THE FUTURE

Entdecken Sie den MSI MAG 275CQPFDE Gaming Monitor. Dieser hochmoderne Monitor verfügt über ein 27" WQHD-Display mit einer blitzschnellen Bildwiederholrate von 180 Hz und einer schnellen Reaktionszeit von 0,5 ms. Mit dem MAG 275CQPFDE haben Sie den Wettbewerbsvorteil, den Sie brauchen, um Ihre Gegner in Gaming-Schlachten zu übertreffen und zu besiegen.



Picture and logos

SELLING POINTS

- Rapid VA Panel – Reaktionszeit von 0.5ms (GtG, Min.) und optimiert die Bildschirmfarben und die Helligkeit
- 180Hz Bildwiederholrate – Erlebe flüssiges Gaming mit einer rasanten Bildwiederholrate und Reaktionszeit
- 0.5ms (GtG, Min.) Reaktionszeit – Beseitigt Screen Tearing und ruckelige Bildraten
- AI Vision – Die neue AI Vision-Technologie kann nicht nur Details in dunklen Bereichen erkennen, sondern auch die Gesamthelligkeit verbessern und Farben sättigen
- Less Blue Light – Eine Softwarelösung zur Reduzierung der Lichtemission im blau-violetten Bereich des Blaulichtspektrums



1. 5-Wege Joystick Navigation
2. Stromanschluss
3. 2 x HDMI™ 2.0b(WQHD@144Hz)
4. DisplayPort 1.4
5. Kopfhöreranschluss
6. Kensington Lock



M O N I T O R

MAG 275CQPFDE

M A G 2 7 5 C Q P F

SPECIFICATION

Model	Part No	9S6-3CD04H-066
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	5000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	90~248 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	119%/85%
	NTSC (CIE1931 area percentage/overlap)	93%/82%
	sRGB (CIE1976 area percentage/overlap)	136%/99%
	sRGB (CIE1931 area percentage/overlap)	130%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	117%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	97%/86%
	DCI-P3 (CIE1976 area percentage/overlap)	109%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	96%/92%
	Rec.709 (CIE1976 area percentage/overlap)	136%/99%
	Rec.709 (CIE1931 area percentage/overlap)	130%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	79%/77%
	Rec.2020 (CIE1931 area percentage/overlap)	69%/68%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	External Adaptor 19V 2.58A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



M O N I T O R

MAG 275CQPFDE

MAG 275CQPF

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-20° ~ 20°
	Adjustment (Height)	0 ~ 110 mm
	VESA Mounting	75x75mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	611.5 x 236.7 x 428.7
	Product Dimension without Stand (WxDxH) (mm)	611.5 x 99.7 x 364.1
	Stand Dimension (WxDxH) (mm)	508.1 x 236.7 x 394.4
	Weight (Net kg)	5.7
	Weight Without Stand (kg)	3.8
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	82.1 x 14.7 x 46.1
	Outer Carton Dimension (WxDxH) (cm)	83.6 x 16.1 x 48.5
	Weight (Gross kg)	8.38
Barcode Info	EAN	4711377330916