

PATH TO THE FUTURE

Visualisiere deinen Sieg mit dem MSI MAG 276CPXFDE Gaming Monitor. Ausgestattet mit 280Hz Bildwiederholrate und 0,5ms Reaktionszeit, gibt dir der MAG 276CPXFDE genau den kompetitiven Vorteil den du brauchst, um deine Gegner zu besiegen. Durch die Adaptive-Sync- Technologie wird die Bildwiederholrate des Monitors mit der GPU synchronisiert für eine fesselnde Gaming-Erfahrung ohne Tearing. Sei dir sicher, dass du dein Ziel triffst.



Picture and logos

SELLING POINTS

- Rapid VA Panel - Bietet eine Reaktionszeit von 0,5 ms (GtG, Min.), optimiert die Bildschirmfarben und die Helligkeit.
- 280Hz Bildwiederholrate - Schnellere Reaktion mit flüssigeren Bildern.
- 0,5ms (GtG, Min.) Reaktionszeit - Verhindert Bildschirmrisse und ruckelige Bildraten.
- AI Vision - Die neue AI Vision-Technologie kann nicht nur Details in dunklen Bereichen sichtbar machen, sondern auch die Gesamthelligkeit und Farbsättigung verbessern.
- Less Blue Light - Verwenden Sie eine Softwarelösung um die Lichtemission blauen Lichts zu reduzieren.



1. 5-Wege Joystick Navigation
2. Stromanschluss
3. 2x HDMI™ 2.0b (FHD@240Hz)
4. Display Port 1.4a
5. Kopfhörerausgang
6. Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3CE04M-024
	Entity MKT Name	MAG 276CPXFDE
	Part No	9S6-3CE04M-024
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~280Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	53.04~1434.72 KHz(H) / 48~280 Hz(V)
	Refresh Rate	280Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	88%/75%
	NTSC (CIE1931 area percentage/overlap)	70%/67%
	sRGB (CIE1976 area percentage/overlap)	102%/94%
	sRGB (CIE1931 area percentage/overlap)	102%/94%
	Adobe RGB (CIE1976 area percentage/overlap)	87%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	74%/72%
	DCI-P3 (CIE1976 area percentage/overlap)	80%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	74%/73%
	Rec.709 (CIE1976 area percentage/overlap)	102%/94%
	Rec.709 (CIE1931 area percentage/overlap)	102%/94%
	Rec.2020 (CIE1976 area percentage/overlap)	57%/57%
	Rec.2020 (CIE1931 area percentage/overlap)	50%/50%
Surface Treatment	Anti-glare	
Display Colors	1.07B	
Color bit	10 bits (8 bits + FRC)	
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	610.5 x 278.3 x 547.6
	Product Dimension without Stand (WxDxH) (mm)	610.5 x 90.4 x 362.5
	Stand Dimension (WxDxH) (mm)	549.9 x 278.3 x 413.3
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	81 x 15 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	83 x 17 x 50.8
	Weight (Gross kg)	N/A
Barcode Info	EAN	471137722297