

## PATH TO THE FUTURE

Entdecken Sie den MSI MAG 276CXFDE Gaming Monitor. Dieser hochmoderne Monitor verfügt über ein 27" FHD-Display mit einer blitzschnellen Bildwiederholrate von 280 Hz und einer schnellen Reaktionszeit von 0,5 ms. Mit dem MAG 276CXFDE haben Sie den Wettbewerbsvorteil, den Sie brauchen, um Ihre Gegner in Gaming-Schlachten zu übertreffen und zu besiegen.



Picture and logos

## SELLING POINTS

- Rapid-VA-Panel – Bietet 0,5 ms (GtG, Min.) Reaktionszeit, optimiert Farben und Helligkeit.
- 280 Hz Bildwiederholrate – Sorgt für schnellere Reaktionen und flüssigere Bilder.
- 0,5 ms (GtG, Min.) Reaktionszeit – Vermeidet Tearing und ruckelige Bildraten.
- AI Vision – Die neue AI Vision-Technologie enthüllt Details in dunklen Bereichen, verbessert die Helligkeit und sorgt für satte Farben.
- Weniger Blaulicht – Reduziert Blaulicht-Emissionen im blau-violetten Spektrum dank intelligenter Softwarelösung.



1. 5-Wege Joystick Navigation
2. Stromanschluss
3. 2x HDMI™ 2.0b(FHD@240Hz)
4. Display Port 1.4a
5. Kopfhörerausgang
6. Kensington Lock

## SPECIFICATION

|                |                                             |                                     |
|----------------|---------------------------------------------|-------------------------------------|
| Model          | SKU Number                                  | 9S6-3CE01M-015                      |
|                | Entity MKT Name                             | MAG 276CXFDE                        |
|                | Part No                                     | 9S6-3CE01M-015                      |
|                | Color                                       | ID1/Black-Black                     |
| Display        | Screen Size                                 | 27" (69 cm)                         |
|                | Active Display Area (mm)                    | 597.888(H)x336.312(V)               |
|                | Curvature                                   | Curve 1500R                         |
|                | Panel Type                                  | Rapid VA                            |
|                | Resolution                                  | 1920x1080 (FHD)                     |
|                | Pixel pitch (mm)                            | 0.3114(H)x0.3114(V)                 |
|                | Aspect Ratio                                | 16:9                                |
|                | Dynamic Refresh Rate technology             | Adaptive-Sync                       |
|                | Dynamic Refresh Rate Activated Range        | 48~280Hz                            |
|                | HDR (High dynamic range)                    | HDR Ready                           |
|                | SDR Brightness (nits)                       | 300                                 |
|                | Contrast Ratio                              | 4000:1                              |
|                | DCR (Dynamic Contrast Ratio)                | 100000000:1                         |
|                | Signal Frequency                            | 53.04~1434.72 KHz(H) / 48~280 Hz(V) |
|                | Refresh Rate                                | 280Hz                               |
|                | Response Time (MPRT)                        | 1ms(MPRT)                           |
|                | Response Time (GTG)                         | 0.5ms                               |
|                | View Angles                                 | 178°(H)/178°(V)                     |
|                | NTSC (CIE1976 area percentage/overlap)      | 88%/75%                             |
|                | NTSC (CIE1931 area percentage/overlap)      | 70%/67%                             |
|                | sRGB (CIE1976 area percentage/overlap)      | 102%/94%                            |
|                | sRGB (CIE1931 area percentage/overlap)      | 102%/94%                            |
|                | Adobe RGB (CIE1976 area percentage/overlap) | 87%/80%                             |
|                | Adobe RGB (CIE1931 area percentage/overlap) | 74%/72%                             |
|                | DCI-P3 (CIE1976 area percentage/overlap)    | 80%/78%                             |
|                | DCI-P3 (CIE1931 area percentage/overlap)    | 74%/73%                             |
|                | Rec.709 (CIE1976 area percentage/overlap)   | 102%/94%                            |
|                | Rec.709 (CIE1931 area percentage/overlap)   | 102%/94%                            |
|                | Rec.2020 (CIE1976 area percentage/overlap)  | 57%/57%                             |
|                | Rec.2020 (CIE1931 area percentage/overlap)  | 50%/50%                             |
|                | Surface Treatment                           | Anti-glare                          |
|                | Display Colors                              | 1.07B                               |
|                | Color bit                                   | 10 bits (8 bits + FRC)              |
| Schnittstellen | Headphone-out                               | 1                                   |
|                | Card reader                                 | N/A                                 |
|                | Lock type                                   | Kensington Lock                     |
|                | HDMI                                        | 2                                   |
|                | HDMI version                                | 2.0b                                |
|                | HDMI HDCP version                           | 2.3                                 |
|                | DisplayPort                                 | 1                                   |
|                | DisplayPort version                         | 1.4a                                |
|                | DisplayPort HDCP version                    | 2.3                                 |
| Garantie       | Warranty                                    | 36M                                 |
| Power          | Power Type                                  | Power Cable                         |
|                | Power Input                                 | 100~240V, 50/60Hz                   |
|                | On-mode Power Consumption (KWh/1000h)       | 21                                  |
|                | Annual Energy Consumption (KWh)             | 31                                  |
|                | Standby-mode Power Consumption (W)          | 0.5                                 |
|                | Off-mode Power Consumption (W)              | 0.3                                 |
|                | Energy Efficiency Rating                    | E                                   |
|                | Power Cord Type                             | C13                                 |



MONITOR

MAG 276CXFDE

MAG 276CXFDE

|                                    |                                              |                       |
|------------------------------------|----------------------------------------------|-----------------------|
| Zubehör                            | DisplayPort Cable                            | 1                     |
|                                    | HDMI Cable                                   | 0                     |
|                                    | DVI Cable                                    | 0                     |
|                                    | USB Type A to Type B Cable                   | 0                     |
|                                    | USB Type C to Type A Cable                   | 0                     |
|                                    | USB Type C to Type C Cable                   | 0                     |
|                                    | Thunderbolt Cable                            | 0                     |
|                                    | VGA Cable                                    | 0                     |
|                                    | 3.5mm audio Cable                            | 0                     |
|                                    | 3.5mm combo audio Cable                      | 0                     |
|                                    | 3.5mm Mic Cable                              | 0                     |
|                                    | Power Cord                                   | 1                     |
|                                    | AC Adaptor                                   | 0                     |
|                                    | Quick Guide                                  | 1                     |
|                                    | Warranty Card                                | 0                     |
|                                    | Mouse Bungee Unit                            | 0                     |
| Design                             | Adjustment (Tilt)                            | -5° ~ 20°             |
|                                    | VESA Mounting                                | 100x100mm             |
| Abmessungen & Gewicht (Product)    | Product Dimension with Stand (WxDxH) (mm)    | 610.5 x 249.8 x 451.6 |
|                                    | Product Dimension without Stand (WxDxH) (mm) | 610.5 x 90.4 x 362.5  |
|                                    | Stand Dimension (WxDxH) (mm)                 | 339.8 x 249.7 x 142.7 |
|                                    | Weight (Net kg)                              | 3.95                  |
|                                    | Weight Without Stand (kg)                    | 3.56                  |
| Abmessungen & Gewicht (Verpackung) | Inside Carton Dimension (WxDxH) (cm)         | 68.4 x 15.8 x 47.5    |
|                                    | Outer Carton Dimension (WxDxH) (cm)          | 70.4 x 17.8 x 50.8    |
|                                    | Weight (Gross kg)                            | 6.51                  |
| Barcode Info                       | EAN                                          | 4711377222181         |