

PATH TO THE FUTURE

Der MSI MAG 321UPDE QD-OLED X24 Gaming-Monitor, 32 Zoll atemberaubendes QD-OLED, 3840x2160 (4K UHD) und 240Hz für ultra-flüssige Grafiken. Perfekt für wettbewerbsorientierte Spieler, die nach Immersion suchen.



Picture and logos

SELLING POINTS

- QD-OLED Gen 4 - Top-Bildqualität & schnelle Reaktionszeit
- DarkArmor-Film - 40 % tiefere Schwarztöne, 2,5x kratzfester
- Uniform Luminance - Individuell anpassbare HDR-Kurve für ein konsistentes HDR-Erlebnis
- 5-lagiges QD-OLED Penta Tandem Panel (EL Gen 3) - Bis zu 30 % höhere Lichteffizienz
- MSI OLED Care 2.0 - Schutz vor Einbrennen
- DisplayHDR True Black 500 - Starke HDR-Darstellung
- 1000 Nits Peak - Intensives HDR-Erlebnis
- Delta E ≤ 2 - Hohe Farbgenauigkeit
- VESA ClearMR 13000 - Kristallklare Bewegungen
- 3 Jahre Garantie - Inklusive Einbrennschutz



1. Kopfhörerausgang
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. Display Port 1.4a
4. USB Typ-C (PD 15W)
5. 5-Wege Joysticknavigation
6. Stromanschluss
7. Kensington lock

SPECIFICATION

Model	Part No	9S6-3DD29A-077
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80.01 cm)
	Active Display Area (mm)	699.48(H) x 394.73(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.1814(H)x0.1814(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	VESA DisplayHDR True Black 500
	SDR Brightness (nits)	300
	HDR Brightness (Peak nits)	1300
	Contrast Ratio	1500000:1
	Signal Frequency	560.6~562.6 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120%/93%
	NTSC (CIE1931 area percentage/overlap)	105%/91%
	sRGB (CIE1976 area percentage/overlap)	138%/100%
	sRGB (CIE1931 area percentage/overlap)	148%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118%/97%
	Adobe RGB (CIE1931 area percentage/overlap)	110%/93%
	DCI-P3 (CIE1976 area percentage/overlap)	110%/99%
	DCI-P3 (CIE1931 area percentage/overlap)	109%/99%
	Rec.709 (CIE1976 area percentage/overlap)	138%/100%
	Rec.709 (CIE1931 area percentage/overlap)	148%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80%/80%
	Rec.2020 (CIE1931 area percentage/overlap)	78%/78%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
	Color bit	10 bits
Schnittstellen	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	33
	Annual Energy Consumption (KWh)	33
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	G
	Power Cord Type	C13

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 15°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-10° ~ 10°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	719.1 x 241.9 x 483.9
	Product Dimension without Stand (WxDxH) (mm)	719.1 x 69.3 x 418.3
	Stand Dimension (WxDxH) (mm)	308.7 x 241.9 x 390.8
	Weight (Net kg)	7.7
	Weight Without Stand (kg)	5.0
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	97.5 x 18.5 x 51.5
	Outer Carton Dimension (WxDxH) (cm)	99.5 x 19.5 x 54
	Weight (Gross kg)	12.38
Barcode Info	EAN	4711377410793