



BUSINESS PRODUCTIVITY MONITOR

PRO MAX 271QPX14G

PRO MAX 271QPX14G

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

SPECIFICATION

Model	SKU Number	PROMAX271QPX14G
	Entity MKT Name	PRO MAX 271QPX14G
	Part No	9S6-3PF89A-011
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	590.42(H) x 333.72(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2292(H)x0.2292(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	200
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1500000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.67%/94.41%
	NTSC (CIE1931 area percentage/overlap)	104.57%/92.43%
	sRGB (CIE1976 area percentage/overlap)	138.39%/100%
	sRGB (CIE1931 area percentage/overlap)	147.64%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.62%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109.44%/94.87%
	DCI-P3 (CIE1976 area percentage/overlap)	110.2%/99.07%
	DCI-P3 (CIE1931 area percentage/overlap)	108.83%/98.47%
	Rec.709 (CIE1976 area percentage/overlap)	138.39%/100%
	Rec.709 (CIE1931 area percentage/overlap)	147.64%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.3%/80.3%
	Rec.2020 (CIE1931 area percentage/overlap)	78.08%/78.08%
	Surface Treatment	Anti-Glare Low Reflection
	Display Colors	1.07B
	Color bit	10 bits



Schnittstellen	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2.5Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13
Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 150 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377430005