

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge – dank des schlanken Rahmens an allen vier Seiten kannst du voll und ganz in eine Multi-Display-Konfiguration eintauchen.
- Genieße hochwertige Unterhaltung mit einer flüssigeren Bildwiederholungsrate von 144 Hz.
- Das TÜV-zertifizierte Display schützt deine Augen und sorgt für deren Gesundheit.
- Die MSI EyesErgo-Technik mit Anti-Flicker-Technik hilft, Augenbelastungen und Ermüdungserscheinungen vorzubeugen.
- MSI Eye-Q Check hilft dir dabei, deine Augen selbst zu überprüfen und erinnert dich daran, bei längerer Nutzung des Monitors eine Pause einzulegen.
- Das VESA-montierbare Design sorgt für eine aufgeräumte Einrichtung und verbessert den Komfort und die Organisation für den Benutzer.
- Mit MSI Power Link kannst du deinen MSI-Desktop mit einem einzigen Druck auf den Netzschalter des Monitors einschalten.
- Dank mehrerer Eingangsquellen wie HDMI™-, DisplayPort- und D-Sub- (VGA-) Anschlüssen bleibt die Vielseitigkeit für verschiedene Geräte erhalten.
- Standardmäßiges VESA-montierbares Design und Zubehörschlitz.
- Zwei integrierte Lautsprecher.



1. 5-Wege Navigation
2. 1x Stromanschluss
3. 1x Kopfhörerausgang
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 2.0b (FHD@144Hz)
6. 1x D-Sub (VGA)
7. 1x Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PD1CT-012
	Entity MKT Name	PRO MP242DE E14A
	Part No	9S6-3PD1CT-012
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48-144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	TBD
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	N/A
	NTSC (CIE1931 area percentage/overlap)	N/A
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
	Rec.2020 (CIE1931 area percentage/overlap)	N/A
	Surface Treatment	Anti-glare
Display Colors	16.7M	
Color bit	8 bits (6 bits + FRC)	
Schnittstellen	D-Sub	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Garantie	Warranty	24M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
Power Cord Type	C13	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377334952