

## Slim, Sleek, Smooth



Picture and logos

## SELLING POINTS

- PerfectEdge - Das vierseitige schlanke Rahmen-Design ermöglicht es Benutzern, vollständig in eine Multi-Display-Konfiguration einzutauchen.
- Genießen Sie erstklassige Unterhaltung mit einer Bildwiederholfrequenz von 144 Hz.
- Das TÜV-zertifizierte Display schützt die Augen und fördert deren Gesundheit.
- Die MSI-EyesErgo-Technologie mit Anti-Flicker-Funktion beugt Augenbelastungen und Ermüdungserscheinungen vor.
- Mithilfe der MSI-Eye-Q-Check-Funktion können Sie Ihre Augen selbst überprüfen. Zudem werden Sie daran erinnert, bei längerer Nutzung des Monitors eine Pause einzulegen.
- Das VESA-kompatible Design sorgt für eine übersichtliche Anordnung und verbessert somit den Komfort und die Organisation für den Benutzer.
- Dank MSI Power Link können Sie Ihren MSI-Desktop mit nur einem Tastendruck auf den Netzschalter des Monitors einschalten.
- Sorgen Sie für Vielseitigkeit auf verschiedenen Geräten, indem Sie verschiedene Eingangsquellen wie HDMI™- und DisplayPort-Anschlüsse nutzen.
- Verfügt über standardmäßige VESA-Halterung sowie einen Zubehörschlitz.
- Zwei eingebaute Lautsprecher.



1. 5-Wege Navi Tasten
2. 1x Stromanschluss
3. 1x Kopfhörerausgang
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@144Hz)
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3PD1CT-048
	Color	ID1/White-White
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	54~169.78 KHz(H) /48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	105%/83%
	NTSC (CIE1931 area percentage/overlap)	82%/75%
	sRGB (CIE1976 area percentage/overlap)	121%/100%
	sRGB (CIE1931 area percentage/overlap)	116%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	104%/87%
	Adobe RGB (CIE1931 area percentage/overlap)	86%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	96%/91%
	DCI-P3 (CIE1931 area percentage/overlap)	85%/84%
	Rec.709 (CIE1976 area percentage/overlap)	121%/100%
	Rec.709 (CIE1931 area percentage/overlap)	116%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	70%/70%
	Rec.2020 (CIE1931 area percentage/overlap)	61%/61%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	2.2
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.2
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
Power Cord Type	C13	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	3.1
	Weight Without Stand (kg)	2.7
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	4.8