

## Slim, Sleek, Smooth

Entdecken Sie unseren 144-Hz-Monitor PRO MP245 E14VL mit 23,8-Zoll-Bildschirm, der speziell für Ihre Arbeit und Unterhaltung entwickelt wurde. Mit EyesErgo für mehr Komfort und einer Bildwiederholfrequenz von 144 Hz sowie dem PerfectEdge-Design, das Ihr AIGC-Erlebnis auf ein neues Niveau hebt.



Picture and logos

## SELLING POINTS

- PerfectEdge – Das schlanke 4-seitige Rahmendesign ermöglicht ein immersives Erlebnis, besonders in Multi-Monitor-Setups.
- 144Hz Bildwiederholrate – Genieße hochwertige Unterhaltung mit besonders flüssiger Darstellung.
- TÜV-zertifiziertes Display – Unterstützt den Schutz der Augen und sorgt für ein angenehmeres Seherlebnis.
- MSI EyesErgo Technologie – Anti-Flicker-Technologie hilft, Augenbelastung und Ermüdung zu reduzieren.
- MSI Eye-Q Check – Unterstützt die Selbstüberprüfung der Augen und erinnert bei langer Nutzung daran, Pausen einzulegen.
- VESA-kompatibles Design – Ermöglicht ein aufgeräumtes Setup und verbessert Komfort sowie Organisation am Arbeitsplatz.
- Vielseitige Anschlussmöglichkeiten – Mehrere Eingänge wie HDMI™ und D-Sub (VGA) sorgen für flexible Kompatibilität mit verschiedenen Geräten.
- Standard-VESA-Montage & Zubehör-Slot



1. 5-Wege Navigationstasten
2. Stromanschluss
3. 1x HDMI™ 1.4b (FHD@144Hz)
4. 1x D-Sub (VGA)
5. Kensington Lock

## SPECIFICATION

|                |                                             |                                  |
|----------------|---------------------------------------------|----------------------------------|
| Model          | Part No                                     | 9S6-3PF1CM-003                   |
|                | Color                                       | ID1/Black-Black                  |
| Display        | Screen Size                                 | 23.8" (60.45cm)                  |
|                | Active Display Area (mm)                    | 527.04(H)x296.46(V)              |
|                | Curvature                                   | Flat                             |
|                | Panel Type                                  | VA                               |
|                | Resolution                                  | 1920x1080 (FHD)                  |
|                | Pixel pitch (mm)                            | 0.2745(H)x0.2745(V)              |
|                | Aspect Ratio                                | 16:9                             |
|                | Dynamic Refresh Rate technology             | Adaptive-Sync                    |
|                | Dynamic Refresh Rate Activated Range        | 48~144Hz                         |
|                | SDR Brightness (nits)                       | 300                              |
|                | Contrast Ratio                              | 4000:1                           |
|                | DCR (Dynamic Contrast Ratio)                | 100000000:1                      |
|                | Signal Frequency                            | 52.8~158.4 KHz(H) / 48~144 Hz(V) |
|                | Refresh Rate                                | 144HZ                            |
|                | Response Time (MPRT)                        | 1ms(MPRT)                        |
|                | Response Time (GTG)                         | 4ms                              |
|                | View Angles                                 | 178°(H)/178°(V)                  |
|                | NTSC (CIE1976 area percentage/overlap)      | N/A                              |
|                | NTSC (CIE1931 area percentage/overlap)      | N/A                              |
|                | sRGB (CIE1976 area percentage/overlap)      | N/A                              |
|                | sRGB (CIE1931 area percentage/overlap)      | N/A                              |
|                | Adobe RGB (CIE1976 area percentage/overlap) | N/A                              |
|                | Adobe RGB (CIE1931 area percentage/overlap) | N/A                              |
|                | DCI-P3 (CIE1976 area percentage/overlap)    | N/A                              |
|                | DCI-P3 (CIE1931 area percentage/overlap)    | N/A                              |
|                | Rec.709 (CIE1976 area percentage/overlap)   | N/A                              |
|                | Rec.709 (CIE1931 area percentage/overlap)   | N/A                              |
|                | Rec.2020 (CIE1976 area percentage/overlap)  | N/A                              |
|                | Rec.2020 (CIE1931 area percentage/overlap)  | N/A                              |
|                | Surface Treatment                           | Anti-glare                       |
|                | Display Colors                              | 16.7M                            |
|                | Color bit                                   | 8 bits (6 bits + FRC)            |
| Schnittstellen | D-Sub                                       | 1                                |
|                | Lock type                                   | Kensington Lock                  |
|                | HDMI                                        | 1                                |
|                | HDMI version                                | 1.4b                             |
|                | HDMI HDCP version                           | 2.3                              |
| Garantie       | Warranty                                    | 36M                              |
| Power          | Power Type                                  | External Adaptor 12V 2A          |
|                | Power Input                                 | 100~240V, 50/60Hz                |
|                | On-mode Power Consumption (KWh/1000h)       | 18                               |
|                | Annual Energy Consumption (KWh)             | 26                               |
|                | Standby-mode Power Consumption (W)          | 0.5                              |
|                | Off-mode Power Consumption (W)              | 0.3                              |
|                | Energy Efficiency Rating                    | TBD                              |
|                | Power Cord Type                             | C13 (Optional)                   |



PRO MP245 E14VL

PRO MP245 E14VL

|                                    |                                              |               |
|------------------------------------|----------------------------------------------|---------------|
| Zubehör                            | DisplayPort Cable                            | 0             |
|                                    | HDMI Cable                                   | 1             |
|                                    | DVI Cable                                    | 0             |
|                                    | USB Type A to Type B Cable                   | 0             |
|                                    | USB Type C to Type A Cable                   | 0             |
|                                    | USB Type C to Type C Cable                   | 0             |
|                                    | Thunderbolt Cable                            | 0             |
|                                    | VGA Cable                                    | 0             |
|                                    | 3.5mm audio Cable                            | 0             |
|                                    | 3.5mm combo audio Cable                      | 0             |
|                                    | 3.5mm Mic Cable                              | 0             |
|                                    | Power Cord                                   | optional      |
|                                    | AC Adaptor                                   | 1             |
|                                    | Quick Guide                                  | 1             |
|                                    | Warranty Card                                | 0             |
|                                    | Mouse Bungee Unit                            | 0             |
| Design                             | Adjustment (Tilt)                            | -5° ~ 20°     |
|                                    | VESA Mounting                                | 100x100mm     |
| Abmessungen & Gewicht (Product)    | Product Dimension with Stand (WxDxH) (mm)    | N/A           |
|                                    | Product Dimension without Stand (WxDxH) (mm) | N/A           |
|                                    | Stand Dimension (WxDxH) (mm)                 | N/A           |
|                                    | Weight (Net kg)                              | N/A           |
|                                    | Weight Without Stand (kg)                    | N/A           |
| Abmessungen & Gewicht (Verpackung) | Inside Carton Dimension (WxDxH) (cm)         | N/A           |
|                                    | Outer Carton Dimension (WxDxH) (cm)          | N/A           |
|                                    | Weight (Gross kg)                            | N/A           |
| Barcode Info                       | EAN                                          | 4711377379830 |