

Be Your Window To The World

Der MSI PRO MP245G FHD-Monitor mit HDMI und DisplayPort-Schnittstellen ist durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern mit ihm lässt Sie auch reibungslose Streaming- und Videoerlebnisse genießen.



Picture and logos

SELLING POINTS

- Perfekte 23,8" Bildschirmgröße für Programmieren, Codieren und Webdesign.
- TÜV-zertifiziertes Display sorgt für Schutz und Gesundheit der Augen.
- MSI EyesErgo-Technologie mit Anti-Flicker- und Weniger-Blaulicht-Technologie hilft, Augenbelastung und Ermüdung zu verhindern.
- 100 Hz Bildwiederholfrequenz bietet ein besseres Seherlebnis mit flimmerfreiem Bild.
- MSI Eye-Q Check hilft, die Augen selbst zu überprüfen und erinnert daran, Pausen einzulegen, wenn der Monitor längere Zeit benutzt wird.
- Vielseitigkeit bei verschiedenen Geräten durch Nutzung mehrerer Eingangsquellen wie HDMI™, DisplayPort und D-Sub(VGA)-Anschlüsse.
- VESA-montierbares Design.
- Eingebaute Lautsprecher.
- Nachhaltiges Produktdesign



1. 1x Stromanschluss
2. 1x DisplayPort (1.2a)
3. 1x HDMI™ 1.4b (FHD@100Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Kopfhörerausgang
7. 1x Kensington Lock
8. 1x 5-Wege Navigation

SPECIFICATION

| | | |
|--------------------------|---|------------------------------------|
| Model | Part No | 9S6-3PC1CM-004 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 23.8" (60cm) |
| | Active Display Area (mm) | 527(H) x 296 (V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 1920x1080 (FHD) |
| | Pixel pitch (mm) | 0.2745(H)x0.2745(V) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48 ~ 100Hz |
| | HDR (High dynamic range) | N/A |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 1000:1 |
| | DCR (Dynamic Contrast Ratio) | 10000000:1 |
| | Signal Frequency | 52.416~112.5 KHz(H) / 48~100 Hz(V) |
| | Refresh Rate | 100HZ |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 4ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | 89/84 |
| | NTSC (CIE1931 area percentage/overlap) | 77/75 |
| | sRGB (CIE1976 area percentage/overlap) | 102/94 |
| | sRGB (CIE1931 area percentage/overlap) | 108/98 |
| | Adobe RGB (CIE1976 area percentage/overlap) | 87/84 |
| | Adobe RGB (CIE1931 area percentage/overlap) | 80/77 |
| | DCI-P3 (CIE1976 area percentage/overlap) | 81/80 |
| | DCI-P3 (CIE1931 area percentage/overlap) | 80/80 |
| | Rec.709 (CIE1976 area percentage/overlap) | 102/94 |
| | Rec.709 (CIE1931 area percentage/overlap) | 108/98 |
| | Rec.2020 (CIE1976 area percentage/overlap) | 59/59 |
| | Rec.2020 (CIE1931 area percentage/overlap) | 57/57 |
| | Surface Treatment | Anti-glare |
| | Display Colors | 16.7M |
| | Color bit | 8 bits (6 bits + FRC) |
| | Schnittstellen | D-Sub |
| Line-in | | 1 |
| Headphone-out | | 1 |
| Card reader | | N/A |
| Lock type | | Kensington Lock |
| HDMI | | 1 |
| HDMI version | | 1.4b |
| HDMI HDCP version | | 1.4 |
| DisplayPort | | 1 |
| DisplayPort version | | 1.2 |
| DisplayPort HDCP version | | 1.3 |
| Garantie | | Warranty |
| Power | Power Type | Power Cable |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 18 |
| | Annual Energy Consumption (KWh) | N/A |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | E |
| Power Cord Type | C13 | |

| | | |
|------------------------------------|--|------------------|
| Zubehör | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 0 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| Mouse Bungee Unit | 0 | |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | VESA Mounting | 100x100mm |
| Abmessungen & Gewicht (Product) | Product Dimension with Stand (WxDxH) (mm) | N/A |
| | Product Dimension without Stand (WxDxH) (mm) | N/A |
| | Stand Dimension (WxDxH) (mm) | N/A |
| | Weight (Net kg) | N/A |
| | Weight Without Stand (kg) | N/A |
| Abmessungen & Gewicht (Verpackung) | Inside Carton Dimension (WxDxH) (cm) | 60 x 12.5 x 40 |
| | Outer Carton Dimension (WxDxH) (cm) | 61.8 x 14.3 x 43 |
| | Weight (Gross kg) | N/A |
| Barcode Info | EAN | 4711377211079 |