

## Slim, Sleek, Smooth

Der beste Home Office Monitor mit elegantem Design. Der PerfectEdge 120Hz Home Office Monitor, der für junge Berufstätige entwickelt wurde, verbindet modernes Design mit hoher Leistung. Ob bei der Erledigung täglicher Büroaufgaben oder beim Eintauchen in fesselnde Spielerlebnisse – dieser Monitor bietet bahnbrechenden visuellen Genuss und Benutzerfreundlichkeit.



Picture and logos

## SELLING POINTS

- PerfectEdge – das 4-seitige Slim-Bezel-Design ermöglicht es Benutzern, vollständig in eine Multi-Display-Konfiguration einzutauchen
- Genieße hochwertige Unterhaltung mit einer flüssigeren Bildwiederholungsrate von 120 Hz.
- 24,5-Zoll-Display mit verbreiterem Rand – Genieße die verbesserte Leinwand auf engstem Raum.
- Die beste Bildschirmgröße für das Büro und den Schreibtisch entspricht der Komfortzone des Betrachters.
- Das TÜV-zertifizierte Display sorgt für den Schutz und die Gesundheit der Augen.
- Die MSI EyesErgo-Technologie mit Anti-Flicker-Technik hilft, Augenbelastung und -ermüdung zu verhindern.
- MSI Eye-Q Check hilft bei der Selbstkontrolle der Augen und erinnert daran, bei längerer Nutzung des Monitors eine Pause einzulegen.
- Erhält die Vielseitigkeit über verschiedene Geräte hinweg durch die Nutzung mehrerer Eingangsquellen, wie HDMI™- und D-Sub-Anschlüsse (VGA).
- Standard-VESA-montierbares Design.



1. 5-Wege Navigation
2. 1x Stromanschluss
3. 1x HDMI™ 1.4b (FHD@120Hz)
4. 1x D-Sub (VGA)
5. 1x Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3PD2CM-035
	Color	ID1/Black-Black
Display	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744 (H) x 302.616 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.704~132.12 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/79%
	NTSC (CIE1931 area percentage/overlap)	73%/71%
	sRGB (CIE1976 area percentage/overlap)	99%/95%
	sRGB (CIE1931 area percentage/overlap)	105%/96%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/83%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/74%
	Rec.709 (CIE1976 area percentage/overlap)	99%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/96%
	Rec.2020 (CIE1976 area percentage/overlap)	57%/57%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
Color bit	8 bits (6 bits + FRC)	
Schnittstellen	D-Sub	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
Garantie	Warranty	24M
Power	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	TBD
	Off-mode Power Consumption (W)	TBD
Energy Efficiency Rating	TBD	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	63 x 11.4 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	64.8 x 13.2 x 44.3
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377316835