

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge, das schlanke 4 Seiten Rahmen Design sorgt für ein nahtloses Seherlebnis in einem Multi Display Setup.
- Genießen Sie hochwertige Unterhaltung mit einer geschmeidigen 144Hz Bildwiederholfrequenz.
- Das TÜV-zertifizierte Display unterstützt den Schutz und die Gesundheit der Augen.
- MSI EyesErgo mit Anti-Flicker-Technik reduziert Bildschirmflimmern und kann die Belastung der Augen sowie Ermüdung bei längerer Nutzung verringern.
- MSI Eye-Q Check ermöglicht die Selbstprüfung der Augen und erinnert daran, Pausen einzulegen, wenn der Monitor längere Zeit genutzt wird.
- Mit MSI Power Link lässt sich dein MSI Desktop mit einem einzigen Klick auf den Netzschalter am Monitor einschalten.
- Flexibilität mit verschiedenen Geräten durch die Nutzung mehrerer Eingangsquellen, wie HDMI™, DisplayPort und D-Sub (VGA) Anschlüssen.
- VESA Standard Montage, integriertes Zubehörschlitz Design.
- Zwei integrierte Lautsprecher.



1. 5-Wege Navigationsjoystick
2. HDMI™ 2.0 (FHD@144Hz)
3. D-Sub (VGA)
4. Line-in
5. Kopfhörerausgang
6. Stromanschluss
7. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PD2CM-076
	Color	ID1/White-White
Display	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744 (H) x 302.616 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~161.7 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	85%/76%
	NTSC (CIE1931 area percentage/overlap)	71%/69%
	sRGB (CIE1976 area percentage/overlap)	99%/93%
	sRGB (CIE1931 area percentage/overlap)	103%/93%
	Adobe RGB (CIE1976 area percentage/overlap)	84%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	75%/71%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	75%/71%
	Rec.709 (CIE1976 area percentage/overlap)	99%/93%
	Rec.709 (CIE1931 area percentage/overlap)	103%/93%
	Rec.2020 (CIE1976 area percentage/overlap)	55%/55%
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	D-Sub	1
	Line-in	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	External Adaptor 12V 3A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13 (Optional)



BUSINESS PRODUCTIVITY MONITOR

PRO MP251W E14A

PRO MP251W E14A

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	optional
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377429269