

Be Your Window To The World

Der MSI PRO MP273QPDE E2 WQHD-Monitor mit DisplayPort- und HDMI- Schnittstellen durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern lässt Sie auch reibungsloseste Streaming- und Videoerlebnisse genießen.



Picture and logos

SELLING POINTS

- Perfekte 27"-Bildschirmgröße mit WQHD(1440p) für den Arbeitsplatz zum Programmieren, Coden und Gestalten von Webseiten
- TÜV-geprüfter Bildschirm zum Schutz der Augen und zur Erhaltung der Sehschärfe
- Die MSI EyesErgo-Technologie mit Anti-Flicker hilft, die Augen zu schonen und Ermüdung vorzubeugen
- 100 Hz Bildwiederholfrequenz sorgen für ein angenehmes Sehgefühl
- Die Less Blue Light PRO-Technologie sorgt für echte Farbtreue und schont die Augen
- MSI Eye-Q Check hilft bei der Selbstkontrolle der Augen und erinnert daran, eine Pause einzulegen, wenn man den Monitor über einen längeren Zeitraum benutzt
- Ein ergonomischer Standfuß, an dem sich ein Mini-PC anbringen lässt, sorgt für ein ergonomischeres und aufgeräumteres Setup und verbessert den Benutzerkomfort sowie Organisation
- Mit mehreren Eingangsquellen wie HDMI™ - und DP-Anschlüssen bist du für alles gerüstet, was du brauchst
- Genießen Sie die sauberste Umgebung mit einem praktischen und abnehmbaren Kabelmanagement
- Standard VESA Design & Zubehörslot
- Zwei eingebaute Lautsprecher



1. 2x HDMI™ (2.0b)
2. 1x DisplayPort (1.2a)
3. 1x Kopfhörerausgang
4. 1x Stromanschluss
5. 1x Kensington Lock
6. OSD Knopf

SPECIFICATION

Model	Part No	9S6-3PB69H-052
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	400
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~160 KHz(H) / 60~144 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	103%/88%
	NTSC (CIE1931 area percentage/overlap)	85%/80%
	sRGB (CIE1976 area percentage/overlap)	118%/99%
	sRGB (CIE1931 area percentage/overlap)	120%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	101%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	94%/85%
	DCI-P3 (CIE1976 area percentage/overlap)	94%/93%
	DCI-P3 (CIE1931 area percentage/overlap)	90%/88%
	Rec.709 (CIE1976 area percentage/overlap)	118%/99%
	Rec.709 (CIE1931 area percentage/overlap)	120%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	External Adaptor 12V 4A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



BUSINESS PRODUCTIVITY MONITOR

PRO MP273QPDE E2

PRO MP273QP E2

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	75x75mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	5.8kg
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	8.9kg
Barcode Info	EAN	4711377170062