

Be Your Window To The World

Der MSI PRO MP273UDE UHD-Monitor mit HDMI und DisplayPort-Schnittstellen ist durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern mit ihm lässt Sie auch reibungsloseste Streaming- und Videoerlebnisse genießen.



Picture and logos

SELLING POINTS

- Perfekte 27" Bildschirmgröße mit UHD (2160p) Auflösung für Programmierung, Videobearbeitung und Webdesign.
- TÜV-zertifiziertes Display gewährleistet den Schutz und die Gesundheit des Sehvermögens.
- MSI EyesErgo-Technologie mit Anti-Flicker-Technologie hilft, Augenbelastung und Müdigkeit zu vermeiden.
- MSI Eye-Q Check ermöglicht die Selbstüberprüfung der Augen und erinnert an Pausen während längerer Nutzung des Monitors.
- Vielseitigkeit für verschiedene Geräte durch die Nutzung mehrerer Eingangsquellen wie HDMI™ und DP-Ports.
- Saubere Umgebung dank praktischem und abnehmbarem Kabelmanagement-Design.
- Standard VESA-montierbar und Zubehörschlitz-Design.
- Zwei integrierte Lautsprecher.



1. 2x HDMI™ (2.0b)
2. 1x DP (1.4a)
3. 1x Kopfhörerausgang
4. 1x Stromanschluss 1x Kensington Lock
5. OSD Knöpfe

SPECIFICATION

Model	SKU Number	9S6-3PB4CH-208
	Part No	9S6-3PB4CH-208
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.1554(H)x0.1554(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	50~60Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	111~138.9 KHz(H) / 50~60 Hz(V)
	Refresh Rate	60Hz
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	113%/90%
	NTSC (CIE1931 area percentage/overlap)	95%/87%
	sRGB (CIE1976 area percentage/overlap)	130%/99%
	sRGB (CIE1931 area percentage/overlap)	136%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	110%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	100%/89%
	DCI-P3 (CIE1976 area percentage/overlap)	103%/98%
	DCI-P3 (CIE1931 area percentage/overlap)	100%/97%
	Rec.709 (CIE1976 area percentage/overlap)	130%/99%
	Rec.709 (CIE1931 area percentage/overlap)	136%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	74%/74%
	Rec.2020 (CIE1931 area percentage/overlap)	70%/70%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
	DisplayPort version	1.4a
Garantie	Warranty	24M
Power	Power Type	External Adaptor 12V 4A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5W
	Off-mode Power Consumption (W)	0.3W
	Energy Efficiency Rating	F
	Power Cord Type	C13



BUSINESS PRODUCTIVITY MONITOR

PRO MP273UDE

PRO MP273U

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	75x75mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	613.50 x 181.10 x 462.60
	Product Dimension without Stand (WxDxH) (mm)	613.50 x 46.60 x 362.50
	Stand Dimension (WxDxH) (mm)	236.20 x 178.70 x 181.10
	Weight (Net kg)	3.95
	Weight Without Stand (kg)	3.5
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	69.7 x 11.9 x 45.8
	Outer Carton Dimension (WxDxH) (cm)	71.2 x 13.2 x 48.2
	Weight (Gross kg)	6.2
Barcode Info	EAN	4711377192279