

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Genieße hochwertige Unterhaltung mit einer flüssigeren Bildwiederholungsrate von 144 Hz.
- Das TÜV-zertifizierte Display sorgt für den Schutz und die Gesundheit deiner Augen.
- Die MSI EyesErgo-Technik mit Anti-Flicker-Technik hilft, Augenbelastungen und Ermüdungserscheinungen vorzubeugen.
- MSI Eye-Q Check hilft dir dabei, deine Augen selbst zu überprüfen und erinnert dich daran, bei längerer Nutzung des Monitors Pausen einzulegen.
- Dank mehrerer Eingangsquellen wie HDMI™-, DP- und D-Sub- (VGA-) Anschlüssen bleibt die Vielseitigkeit für verschiedene Geräte erhalten.
- Genieße eine aufgeräumte Umgebung dank praktischem und abnehmbarem Kabelmanagement-Design.
- Standardmäßige VESA-Montagemöglichkeit und Zubehörschlitz-Design.



1. 5-Wege Navigationstasten
2. 1x DisplayPort 1.2a
3. 1x HDMI™ 2.0 (FHD@144Hz)
4. 1x D-Sub (VGA)
5. 1x Kopfhörerausgang
6. Stromanschluss
7. Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PB4CH-262
	Entity MKT Name	PRO MP273W E14A
	Part No	9S6-3PB4CH-262
	Color	ID1/White-White
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	53.8~143.2 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	89%/74%
	NTSC (CIE1931 area percentage/overlap)	70%/66%
	sRGB (CIE1976 area percentage/overlap)	102%/90%
	sRGB (CIE1931 area percentage/overlap)	99%/88%
	Adobe RGB (CIE1976 area percentage/overlap)	88%/78%
	Adobe RGB (CIE1931 area percentage/overlap)	73%/70%
	DCI-P3 (CIE1976 area percentage/overlap)	82%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	73%/72%
	Rec.709 (CIE1976 area percentage/overlap)	102%/90%
	Rec.709 (CIE1931 area percentage/overlap)	99%/88%
	Rec.2020 (CIE1976 area percentage/overlap)	59%/59%
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	D-Sub	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	3Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
	Warranty	36M
	Garantie	Power Type
Power Input		100~240V, 50/60Hz
On-mode Power Consumption (KWh/1000h)		17
Annual Energy Consumption (KWh)		17
Standby-mode Power Consumption (W)		0.5
Off-mode Power Consumption (W)		0.3
Energy Efficiency Rating		D
Power Cord Type	C13 (Optional)	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	optional
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	613.49 x 201.01 x 470.61
	Product Dimension without Stand (WxDxH) (mm)	613.49 x 59.56 x 364.46
	Stand Dimension (WxDxH) (mm)	240.54 x 201.01 x 178.92
	Weight (Net kg)	4.1
	Weight Without Stand (kg)	3.65
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 45.1
	Outer Carton Dimension (WxDxH) (cm)	70.3 x 14.1 x 47.5
	Weight (Gross kg)	6.3
Barcode Info	EAN	4711377349550