

## Slim, Sleek, Smooth



Picture and logos

## SELLING POINTS

- Genieße erstklassige Unterhaltung mit flüssigen 144 Hz.
- Das TÜV-zertifizierte Display schont deine Augen und unterstützt langfristige Augengesundheit.
- Die MSI EyesErgo- und Anti-Flicker-Technik reduziert Belastung und Ermüdung der Augen.
- MSI Eye-Q Check unterstützt dich bei der Selbstprüfung deiner Augen und erinnert dich bei längerer Nutzung an regelmäßige Pausen.
- Nutze HDMI™- und DP-Anschlüsse für flexible Verbindungen mit verschiedenen Geräten.
- Sorge für Ordnung mit dem praktischen, abnehmbaren Kabelmanagement.
- Standard-VESA-montierbar & Zubehörschlitz-Design.
- Zwei integrierte Lautsprecher.



1. 5-Wege Navi Tasten
2. HDMI™ 2.0 (FHD@144Hz)
3. D-Sub (VGA)
4. Line-in
5. Kopfhörerausgang
6. Stromanschluss
7. Kensington Lock

**SPECIFICATION**

Model	SKU Number	9S6-3PF0CM-003
	Entity MKT Name	PRO MP275 E14L
	Part No	9S6-3PF0CM-003
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	AMD FreeSync™
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.85~158.54 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	95%/75%
	NTSC (CIE1931 area percentage/overlap)	77%/70%
	sRGB (CIE1976 area percentage/overlap)	110%/93%
	sRGB (CIE1931 area percentage/overlap)	110%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	95%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	80%/73%
	DCI-P3 (CIE1976 area percentage/overlap)	88%/85%
	DCI-P3 (CIE1931 area percentage/overlap)	80%/79%
	Rec.709 (CIE1976 area percentage/overlap)	110%/93%
	Rec.709 (CIE1931 area percentage/overlap)	110%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	60%/60%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
Surface Treatment	Anti-glare	
Display Colors	16.7M	
Color bit	8 bits (6 bits + FRC)	
Schnittstellen	D-Sub	1
	Line-in	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	612.1 x 206.8 x 457.3
	Product Dimension without Stand (WxDxH) (mm)	612.1 x 54.6 x 358.8
	Stand Dimension (WxDxH) (mm)	218.8 x 206.8 x 146.2
	Weight (Net kg)	3.94
	Weight Without Stand (kg)	3.57
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 10.3 x 46.2
	Outer Carton Dimension (WxDxH) (cm)	70.8 x 12.3 x 49.2
	Weight (Gross kg)	6.05
Barcode Info	EAN	4711377379717