

Be Your Window To The World

Der MSI PRO MP275PGDE FHD-Monitor mit HDMI und DisplayPort-Schnittstellen ist durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern mit ihm lässt Sie auch reibungsloseste Streaming- und Videoerlebnisse genießen



Picture and logos

SELLING POINTS

- Perfekte 27-Zoll-Bildschirmgröße für Programmierung, Codierung und Webdesign.
- TÜV-zertifiziertes Display gewährleistet den Schutz und die Gesundheit der Augen.
- Die MSI EyesErgo-Technologie mit Anti-Flicker- und Less Blue Light-Technologie hilft, Augenbelastung und Ermüdung zu verhindern.
- Die 100Hz-Bildwiederholrate sorgt für ein besseres Seherlebnis mit flimmerfreien Bildern.
- MSI Eye-Q Check ermöglicht eine Selbstüberprüfung der Augen und erinnert daran, Pausen einzulegen, wenn der Monitor über längere Zeit genutzt wird.
- Der Stand ist mit ergonomischen Merkmalen ausgestattet, darunter Neigungs-, Dreh-, Höhen- und Pivot-Anpassungen.
- Die Vielseitigkeit wird durch die Nutzung mehrerer Eingangsquellen, wie HDMI™, DisplayPort und D-Sub (VGA)-Ports, gewährleistet.
- Standardmäßiges VESA-montierbares Design.
- Zwei integrierte Lautsprecher.
- Eine nachhaltige Lösung zum Schutz der Umwelt.



1. 1x Stromanschluss
2. 1x DisplayPort 1.2a
3. 1x HDMI™ 1.4b (FHD@100Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Kopfhörerausgang
7. 1x Kensington Lock
8. 1x 5-Wege Navigation

SPECIFICATION

Model	SKU Number	9S6-3PC39M-053
	Entity MKT Name	PRO MP275PG
	Part No	9S6-3PC39M-053
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	HDR Brightness (Peak nits)	-
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.7~137.58 KHz (H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	82%,75%
	NTSC (CIE1931 area percentage/overlap)	72%,70%
	sRGB (CIE1976 area percentage/overlap)	95%,90%
	sRGB (CIE1931 area percentage/overlap)	101%,92%
	Adobe RGB (CIE1976 area percentage/overlap)	80%,78%
	Adobe RGB (CIE1931 area percentage/overlap)	74%,70%
	DCI-P3 (CIE1976 area percentage/overlap)	74%,74%
	DCI-P3 (CIE1931 area percentage/overlap)	73%,73%
	Rec.709 (CIE1976 area percentage/overlap)	95%,90%
	Rec.709 (CIE1931 area percentage/overlap)	101%,92%
	Rec.2020 (CIE1976 area percentage/overlap)	51%,51%
	Rec.2020 (CIE1931 area percentage/overlap)	53%,53%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	D-Sub	1
	Line-in	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2x 2W
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Garantie	Warranty	24M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5W
	Off-mode Power Consumption (W)	0.3W
	Energy Efficiency Rating	E
	Power Cord Type	C13

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	612.1 x 226.9 x 561.4
	Product Dimension without Stand (WxDxH) (mm)	612.1 x 56.1 x 363.0
	Stand Dimension (WxDxH) (mm)	259.7 x 226.9 x 411.5
	Weight (Net kg)	6.03
	Weight Without Stand (kg)	3.43
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	8.95
Barcode Info	EAN	4711377219167