

## Business & Productivity Monitor



Picture and logos

### SELLING POINTS

- 21:9 UWQHD-34"-Bildschirm verbessert Multitasking und erweitert Ihren Horizont.
- Die 1500R-Krümmung sorgt für ein besonders immersives Seherlebnis bei der Arbeit und im Alltag.
- Genießen Sie hochwertige Unterhaltung mit einer flüssigen Bildwiederholrate von 120 Hz.
- Das TÜV-zertifizierte Display schont Ihre Augen.
- Die MSI EyeSergo-Technik mit Anti-Flicker-Technik hilft, Augenbelastungen und Ermüdungserscheinungen vorzubeugen.
- MSI Eye-Q Check hilft dir dabei, deine Augen selbst zu überprüfen und erinnert dich daran, bei längerer Nutzung des Monitors Pausen einzulegen.
- Genieße eine aufgeräumte Umgebung dank praktischem und abnehmbarem Kabelmanagement und Standard-Vesa Design.
- MSI Power Link ermöglicht das Einschalten Ihres MSI-Desktops mit einem einzigen Druck auf den Netzschalter des Monitors.
- Mit mehreren Eingangsquellen wie HDMI™ - und DP-Anschlüssen sind Sie für alles gerüstet, was Sie brauchen
- Zwei eingebaute Lautsprecher.



1. OSD Knöpfe
2. Stromanschluss
3. 2x HDMI™ 2.0b (UWQHD@100Hz)
4. 1x DisplayPort 1.4a
5. Kopfhörerausgang
6. Kensington Lock

**SPECIFICATION**

Model	SKU Number	9S6-3PB2CT-048
	Entity MKT Name	PRO MP341CQDE E12
	Part No	9S6-3PB2CT-048
	Color	ID1/Black-Black
Display	Screen Size	34" (86.36 cm)
	Active Display Area (mm)	797.22(H) x 333.72(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	3440x1440 (UWQHD)
	Pixel pitch (mm)	0.23175(H)x0.23175(V)
	Aspect Ratio	21:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	70.73~178.8 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/86%
	NTSC (CIE1931 area percentage/overlap)	86%/80%
	sRGB (CIE1976 area percentage/overlap)	114%/98%
	sRGB (CIE1931 area percentage/overlap)	121%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/89%
	Adobe RGB (CIE1931 area percentage/overlap)	90%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	91%/91%
	DCI-P3 (CIE1931 area percentage/overlap)	90%/90%
	Rec.709 (CIE1976 area percentage/overlap)	114%/98%
	Rec.709 (CIE1931 area percentage/overlap)	121%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	66%/66%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
Surface Treatment	Anti-glare	
Display Colors	1.07B	
Color bit	10 bits (8 bits + FRC)	
Schnittstellen	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR2)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	SDR:25 HDR:50
	Annual Energy Consumption (KWh)	44
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
Power Cord Type	C13	

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-3.5° ~ 21.5°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	809.34 x 237 x 469.54
	Product Dimension without Stand (WxDxH) (mm)	809.34 x 106.79 x 365.84
	Stand Dimension (WxDxH) (mm)	210 x 237 x 176.57
	Weight (Net kg)	7.1
	Weight Without Stand (kg)	6
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	98.5 x 19.8 x 49
	Outer Carton Dimension (WxDxH) (cm)	100 x 21.3 x 51.3
	Weight (Gross kg)	11.1
Barcode Info	EAN	4711377395526